



Notice

The company reserves the right to revise this publication or to change its contents without notice. Information contained herein is for reference only and does not constitute a commitment on the part of the manufacturer or any subsequent vendor. They assume no responsibility or liability for any errors or inaccuracies that may appear in this publication nor are they in anyway responsible for any loss or damage resulting from the use (or misuse) of this publication.

This publication and any accompanying software may not, in whole or in part, be reproduced, translated, transmitted or reduced to any machine readable form without prior consent from the vendor, manufacturer or creators of this publication, except for copies kept by the user for backup purposes.

Brand and product names mentioned in this publication may or may not be copyrights and/or registered trademarks of their respective companies. They are mentioned for identification purposes only and are not intended as an endorsement of that product or its manufacturer.

©August 2011

Trademarks

Intel and Intel Core are trademarks/registered trademarks of Intel Corporation.

R&TTE Directive

This device is in compliance with the essential requirements and other relevant provisions of the R&TTE Directive 1999/5/EC.

This device will be sold in the following EEA countries: Austria, Italy, Belgium, Liechtenstein, Denmark, Luxembourg, Finland, Netherlands, France, Norway, Germany, Portugal, Greece, Spain, Iceland, Sweden, Ireland, United Kingdom, Cyprus, Czech Republic, Estonia, Hungary, Latvia, Lithuania, Malta, Slovakia, Poland, Slovenia.

CE Marking

This device has been tested to and conforms to the regulatory requirements of the European Union and has attained CE Marking. The CE Mark is a conformity marking consisting of the letters "CE". The CE Mark applies to products regulated by certain European health, safety and environmental protection legislation. The CE Mark is obligatory for products it applies to: the manufacturer affixes the marking in order to be allowed to sell his product in the European market.

This product conforms to the essential requirements of the R&TTE directive 1999/5/EC in order to attain CE Marking. A notified body has determined that this device has properly demonstrated that the requirements of the directive have been met and has issued a favorable certificate of expert opinion. As such the device will bear the notified body number 0560 after the CE mark.

The CE Marking is not a quality mark. Foremost, it refers to the safety rather than to the quality of a product. Secondly, CE Marking is mandatory for the product it applies to, whereas most quality markings are voluntary.

FCC Statement (Federal Communications Commission)

You are cautioned that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Re orient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the service representative or an experienced radio/TV technician for help.

Operation is subject to the following two conditions:

1. This device may not cause interference.

And

2. This device must accept any interference, including interference that may cause undesired operation of the device.

FCC RF Radiation Exposure Statement:

- 1. This Transmitter must not be co-located or operating in conjunction with any other antenna or transmitter.
- 2. This equipment complies with FCC RF radiation exposure limits set forth for an uncontrolled environment. This equipment should be installed and operated with a minimum distance of 20 centimeters between the radiator and your body.

が Warning

Use only shielded cables to connect I/O devices to this equipment. You are cautioned that changes or modifications not expressly approved by the manufacturer for compliance with the above standards could void your authority to operate the equipment.

EuP Off Mode Power Consumption Statement:

The figures below note the power consumption of this computer in compliance with European Commission (EC) regulations on power consumption in off mode:

• Off Mode < 1W

IMPORTANT SAFETY INSTRUCTIONS

Follow basic safety precautions, including those listed below, to reduce the risk of fire, electric shock, and injury to persons when using any electrical equipment:

- 1. Do not use this product near water, for example near a bath tub, wash bowl, kitchen sink or laundry tub, in a wet basement or near a swimming pool.
- 2. Avoid using this equipment with a telephone line (other than a cordless type) during an electrical storm. There may be a remote risk of electrical shock from lightning.
- 3. Do not use the telephone to report a gas leak in the vicinity of the leak.
- 4. Use only the power cord and batteries indicated in this manual. Do not dispose of batteries in a fire. They may explode. Check with local codes for possible special disposal instructions.
- 5. This product is intended to be supplied by a Listed Power Unit (Full Range AC/DC Adapter AC Input 100 240V, 50 60Hz DC Output 19V, 11.57A (**220W**) minimum).

This Computer's Optical Device is a Laser Class 1 Product

Instructions for Care and Operation

The notebook computer is quite rugged, but it can be damaged. To prevent this, follow these suggestions:


1. Don't drop it, or expose it to shock. If the computer falls, the case and the components could be damaged.




Keep it dry, and don't overheat it. Keep the computer and power supply away from any kind of heating element. This is an electrical appliance. If water or any other liquid gets into it, the computer could be badly damaged.



- 3. **Avoid interference.** Keep the computer away from high capacity transformers, electric motors, and other strong magnetic fields. These can hinder proper performance and damage your data.
- 4. **Follow the proper working procedures for the computer.** Shut the computer down properly and don't forget to save your work. Remember to periodically save your data as data may be lost if the battery is depleted.



5. Take care when using peripheral devices.




Power Safety

The computer has specific power requirements:

Power Safety Warning

Before you undertake any upgrade procedures, make sure that you have turned off the power, and disconnected all peripherals and cables (including telephone lines). It is advisable to also remove your battery in order to prevent accidentally turning the machine on.

- Only use a power adapter approved for use with this computer.
- Your AC/DC adapter may be designed for international travel but it still requires a steady, uninterrupted power supply. If you are unsure of your local power specifications, consult your service representative or local power company.
- The power adapter may have either a 2-prong or a 3-prong grounded plug. The third prong is an important safety feature; do not defeat its purpose. If you do not have access to a compatible outlet, have a qualified electrician install one.
- When you want to unplug the power cord, be sure to disconnect it by the plug head, not by its wire.
- Make sure the socket and any extension cord(s) you use can support the total current load of all the connected devices.
- Before cleaning the computer, make sure it is disconnected from any external power supplies (i.e. AC/DC adapter or car adapter).



Polymer Battery Precautions

Note the following information which is specific to polymer batteries only, and where applicable, this overrides the general battery precaution information overleaf.

- Polymer batteries may experience a slight expansion or swelling, however this is part of the battery's safety mechanism and is not a cause for concern.
- Use proper handling procedures when using polymer batteries. Do not use polymer batteries in high ambient temperature environments, and do not store unused batteries for extended periods.

See also the general battery precautionary information overleaf for further information.

Battery Precautions

- Only use batteries designed for this computer. The wrong battery type may explode, leak or damage the computer.
- Do not remove any batteries from the computer while it is powered on.
- Do not continue to use a battery that has been dropped, or that appears damaged (e.g. bent or twisted) in any way. Even if the computer continues to work with a damaged battery in place, it may cause circuit damage, which may possibly result in fire.
- If you do not use the battery for an extended period, then remove the battery from the computer for storage.
- Recharge the batteries using the notebook's system. Incorrect recharging may make the battery explode.
- Do not try to repair a battery pack. Refer any battery pack repair or replacement to your service representative or qualified service personnel.
- Keep children away from, and promptly dispose of a damaged battery. Always dispose of batteries carefully. Batteries may explode or leak if exposed to fire, or improperly handled or discarded.
- Keep the battery away from metal appliances.
- Affix tape to the battery contacts before disposing of the battery.
- Do not touch the battery contacts with your hands or metal objects.

泛

Battery Disposal & Caution

The product that you have purchased contains a rechargeable battery. The battery is recyclable. At the end of its useful life, under various state and local laws, it may be illegal to dispose of this battery into the municipal waste stream. Check with your local solid waste officials for details in your area for recycling options or proper disposal.

Danger of explosion if battery is incorrectly replaced. Replace only with the same or equivalent type recommended by the manufacturer. Discard used battery according to the manufacturer's instructions.

Cleaning

Do not apply cleaner directly to the computer; use a soft clean cloth. Do not use volatile (petroleum distillates) or abrasive cleaners on any part of the computer.

Servicing

Do not attempt to service the computer yourself. Doing so may violate your warranty and expose you and the computer to electric shock. Refer all servicing to authorized service personnel. Unplug the computer from the power supply. Then refer servicing to qualified service personnel under any of the following conditions:

- When the power cord or AC/DC adapter is damaged or frayed.
- If the computer has been exposed to rain or other liquids.
- If the computer does not work normally when you follow the operating instructions.
- If the computer has been dropped or damaged (do not touch the poisonous liquid if the LCD panel breaks).
- If there is an unusual odor, heat or smoke coming from your computer.

Removal Warning

When removing any cover(s) and screw(s) for the purposes of device upgrade, remember to replace the cover(s) and screw(s) before turning the computer on.

Travel Considerations

Packing

As you get ready for your trip, run through this list to make sure the system is ready to go:

- 1. Check that the battery pack and any spares are fully charged.
- 2. Power off the computer and peripherals.
- 3. Close the display panel and make sure it's latched.
- 4. Disconnect the AC/DC adapter and cables. Stow them in the carrying bag.
- 5. The AC/DC adapter uses voltages from 100 to 240 volts so you won't need a second voltage adapter. However, check with your travel agent to see if you need any socket adapters.
- 6. Put the notebook in its carrying bag and secure it with the bag's straps.
- 7. If you're taking any peripherals (e.g. a printer, mouse or digital camera), pack them and those devices' adapters and/or cables.
- 8. Anticipate customs Some jurisdictions may have import restrictions or require proof of ownership for both hardware and software. Make sure your "papers" are handy.

Power Off Before Traveling

Make sure that your notebook is completely powered off before putting it into a travel bag (or any such container). Putting a notebook which is powered on in a travel bag may cause the Vents/Fan Intakes to be blocked. To prevent your computer from overheating make sure nothing blocks the Vent/Fan Intakes while the computer is in use.

On the Road

In addition to the general safety and maintenance suggestions in this preface, and Chapter 8: Troubleshooting, keep these points in mind:

Hand-carry the notebook - For security, don't let it out of your sight. In some areas, computer theft is very common. Don't check it with "normal" luggage. Baggage handlers may not be sufficiently careful. Avoid knocking the computer against hard objects.

Beware of Electromagnetic fields - Devices such as metal detectors & X-ray machines can damage the computer, hard disk, floppy disks, and other media. They may also destroy any stored data - Pass your computer and disks around the devices. Ask security officials to hand-inspect them (you may be asked to turn it on). **Note**: Some airports also scan luggage with these devices.

Fly safely - Most airlines have regulations about the use of computers and other electronic devices in flight. These restrictions are for your safety, follow them. If you stow the notebook in an overhead compartment, make sure it's secure. Contents may shift and/or fall out when the compartment is opened.

Get power where you can - If an electrical outlet is available, use the AC/DC adapter and keep your battery(ies) charged.

Keep it dry - If you move quickly from a cold to a warm location, water vapor can condense inside the computer. Wait a few minutes before turning it on so that any moisture can evaporate.

Developing Good Work Habits

Developing good work habits is important if you need to work in front of the computer for long periods of time. Improper work habits can result in discomfort or serious injury from repetitive strain to your hands, wrists or other joints. The following are some tips to reduce the strain:



- Adjust the height of the chair and/or desk so that the keyboard is at or slightly below the level of your elbow. Keep your forearms, wrists, and hands in a relaxed position.
- Your knees should be slightly higher than your hips. Place your feet flat on the floor or on a footrest if necessary.
- Use a chair with a back and adjust it to support your lower back comfortably.
- Sit straight so that your knees, hips and elbows form approximately 90-degree angles when you are working.
- Take periodic breaks if you are using the computer for long periods of time.



Remember to:

- Alter your posture frequently.
- Stretch and exercise your body several times a day.
- Take periodic breaks when you work at the computer for long periods of time. Frequent and short breaks are better than fewer and longer breaks.

Lighting

Proper lighting and a comfortable viewing angle can reduce eye strain and shoulder and neck muscle fatigue.

- Position the display to avoid glare or reflections from overhead lighting or outside sources of light.
- Keep the display screen clean and set the brightness and contrast to levels that allow you to see the screen clearly.
- Position the display directly in front of you at a comfortable viewing distance.
- Adjust the display-viewing angle to find the best position.

LCD Screen Care

To prevent **image persistence** on LCD monitors (caused by the continuous display of graphics on the screen for an extended period of time) take the following precautions:

- Set the Windows Power Plans to turn the screen off after a few minutes of screen idle time.
- Use a rotating, moving or blank screen saver (this prevents an image from being displayed too long).
- Rotate desktop background images every few days.
- Turn the monitor off when the system is not in use.

LCD Electro-Plated Logos

Note that in computers featuring a raised LCD electro-plated logo, the logo is covered by a protective adhesive. Due to general wear and tear, this adhesive may deteriorate over time and the exposed logo may develop sharp edges. Be careful when handling the computer in this case, and avoid touching the raised LCD electro-plated logo. Avoid placing any other items in the carrying bag which may rub against the top of the computer during transport. If any such wear and tear develops contact your service center.

Contents

NoticeI
FCC Statement III
FCC RF Radiation Exposure Statement:IV
EuP Off Mode Power Consumption Statement:IV
Instructions for Care and OperationVI
Power Safety VIII
Polymer Battery PrecautionsIX
Battery PrecautionsX
CleaningXI
ServicingXI
Travel ConsiderationsXII

Quick Start Guide

Overview	1-1
Advanced Users	1-2
Beginners and Not-So-Advanced Users	1-2
Warning Boxes	1-2
Not Included	1-3
System Software	1-4
RAID & AHCI Setup	1-4
System Startup	1-5
System Map: LCD Panel Open & Top View	1-6
LED Indicators	1-7

Game Keys	1-8
Touch Sensor Instant Keys	1-9
Keyboard	1-10
Function Keys & Visual Indicators	1-11
System Map: Front & Rear Views	1-12
System Map: Right View	1-13
System Map: Left View	1-14
System Map: Bottom View	1-16
Video Features	
Screen Resolution	1-19
NVIDIA Control Panel	
Power Options	1-21

Storage Devices, Mouse, Audio & Printer

Overview	2-1
Hard Disk Drive	2-2
Optical Device	2-3
Loading Discs	2-3
Handling CDs or DVDs	2-4
DVD Regional Codes	2-5
Multi-In-1 Card Reader	2-6
ExpressCard Slot	2-7

Inserting and Removing ExpressCards	2-7
Game Keys	
Audio Features	
Setup for Audio Recording	2-10
Suppressing Audio Background Noise	2-11
Setup for 5.1 or 7.1 Surround Sound	2-13
TouchPad and Buttons/Mouse	2-15
Gestures and Device Settings	2-16
Adding a Printer	2-19
USB Printer	2-19
Install Instructions:	2-19
Parallel Printer	2-19

Power Management

Overview	3-1
The Power Sources	3-2
AC/DC Adapter	
Battery	3-2
Turning On the Computer	3-3
Power Plans	3-4
Power-Saving States	3-6
Sleep	3-6
Hibernate	3-7
Shut down	3-7
Configuring the Power Buttons	3-8

Resuming Operation	3-9
Battery Information	3-10
Conserving Battery Power	3-11
Battery Life	3-12
New Battery	3-12
Recharging the Battery with the AC/DC Adapter	3-12
Proper handling of the Battery Pack	3-13
Battery FAQ	3-14

Drivers & Utilities

RAID & AHCI Setup	4-1
What to Install	4-1
Module Driver Installation	4-1
Driver Installation	4-2
Manual Driver Installation	4-4
Updating/Reinstalling Individual Drivers	4-4
User Account Control	
Windows Security Message	4-5
New Hardware Found	4-5
Driver Installation Procedure	4-6
Chipset	
Video (VGA)	
LAN	
Card Reader	4-7
TouchPad	

Hot Key	4-7
GameKey Utility	4-7
USB 3.0	4-7
MEI Driver	
Audio	
Optional Drivers	4-9
PC Camera	4-10
Wireless LAN	4-10
Fingerprint Reader Module	4-10
Bluetooth Module	4-10

BIOS Utilities

Overview	5-1
The Power-On Self Test (POST)	
Failing the POST	5-3
Fatal Errors	5-3
Non-Fatal Errors	5-3
The Setup Utility	
Entering Setup	
Setup Screens	
Main Menu	
System Time & Date (Main Menu)	
SATA Port 0/1/2/3/4 (Main Menu)	5-7
System/Extended Memory (Main Menu)	5-7
BIOS Revision/ KBC/EC firmware Revision /	

VGA Card etc. (Main Menu)	5-7
Advanced Menu	5-8
Advanced Chipset Control (Advanced Menu)	5-8
Bluetooth Power Setting (Advanced Menu >	
Advanced Chipset Control)	5-9
SATA Mode (Advanced Menu)	5-9
Legacy USB Support: (Advanced Menu)	5-9
Boot Logo: (Advanced Menu)	5-9
Power On Boot Beep (Advanced Menu)	5-10
Battery Low Alarm Beep (Advanced Menu)	5-10
Security Menu	5-11
Set Supervisor Password (Security Menu)	5-11
Boot Menu	5-12
Boot Sequence (Boot Menu)	5-13
Exit Menu	

Upgrading The Computer

Overview	6-1
When Not to Upgrade	6-2
Removing the Battery	6-3
Upgrading the Optical (CD/DVD) Device	6-4
Upgrading the Hard Disk Drive(s)	6-5
Upgrading the System Memory (RAM)	6-10
Upgrading the Video Card	6-20

Modules

Overview	7-1
Setting Up SATA RAID or AHCI Mode	7-2
AHCI Mode	
RAID	7-2
Intel® Rapid Storage Technology Application	7-2
SATA RAID Setup Procedure (BIOS)	
RAID Setup (Intel Matrix)	
Intel Rapid Storage Technology	
IRST Driver Installation	
RAID Volume Data Verification and Repair	7-12
Replacing and Reverting Recovery and	
Master Volumes	7-12
PC Camera Module	7-15
PC Camera Driver Installation	7-16
PC Camera Audio Setup	7-17
Wireless LAN Module	
Intel® Wi-Fi Link Series Driver Installation	7-24
802.11b/g/n Driver Installation	7-24
Connecting to a Wireless Network in Windows 7.	7-25
Intel® My WiFi Configuration	7-28
Intel WLAN & Bluetooth Combo Module	
High-Speed Data Transfer Configuration	7-40
Windows Mobility Center	
Fingerprint Reader Module	

Fingerprint Reader Driver Installation	7-44
User Enrollment	7-45
Fingerprint Control Center Features	7-48
Bluetooth Module	7-49
3rd Party Bluetooth Combo Driver Installation	7-51
3rd Party Bluetooth & WLAN Combo Settings	7-52
3rd Party Bluetooth Networking Setup	7-55
3rd Party Bluetooth & WLAN Combo Module	
Configuration	7-56
Intel Bluetooth Combo Driver Installation	7-59
Standard Bluetooth Configuration in Windows 7	7-60
THX TruStudio Pro Audio	7-64
THX TruStudio AP Installation	7-64
THX TruStudio Pro Activation	7-65
THX TruStudio Pro Application	7-65

Troubleshooting

Overview	8-1
Basic Hints and Tips	8-2
Backup and General Maintenance	8-3
Viruses	8-4
Upgrading and Adding New Hardware/Software	8-5
Problems & Possible Solutions	8-7
Bluetooth Connection Problems	8-14
Intel® Centrino Advanced WLAN &	

Bluetooth V3.0+HS Combo Modules8	-18
Installing Windows 7 (pre Service Pack 1) for	
RAID Systems with Advanced Format Disks	-19

Interface (Ports & Jacks)

Overview	A-1
Ports and Jacks	A-2
Card Reader	A-2
DC-In Jack	
DVI-Out Port	
e-SATA/USB Port	A-2
HDMI-Out Port	
Headphone-Out Jack	
Line-In Jack	
Microphone-In Jack	A-3
Mini-IEEE 1394 Port	A-4
RJ-45 LAN Jack	A-4
S/PDIF-Out Jack	A-4
Security Lock Slot	A-4
USB 2.0/1.1 Ports*	A-5
USB 3.0 Port	A-5

NVIDIA Video Driver Controls

NVIDIA Video Driver Installation	B-1
NVIDIA Control Panel	B-2

Display Devices	B-5
Display Modes	B-6
Configuring an External Display (NVIDIA)	B-7
Attaching Other Displays (Win 7)	B-11
SLI Multi GPU Configuration	B-14
SLI Multi GPU Configuration & Battery Power	B-15
Manage 3D Settings	B-16
Adjust Video Settings	B-17
HDMI Audio Configuration	B-18
HDCP Status	B-22

Specifications

L	
Processor	C-2
Core Logic	C-2
Display	C-2
Memory	C-2
Video Adapter Options	
BIOS	C-2
Storage	C-2
Audio	C-3
Keyboard & Pointing Device	C-3
Card Reader	C-3
Slots	C-3
Interface	C-3
Communication	C-4

Security	C-4
Operating System	
Power Management	
Power	
Environmental Spec	C-4
Physical Dimensions & Weight	C-4

Chapter 1: Quick Start Guide

Overview

This Quick Start Guide is a brief introduction to the basic features of your computer, to navigating around the computer and to getting your system started. The remainder of the manual covers the following:

- Chapter 2 A guide to using some of the main features of the computer e.g. the storage devices (hard disk, optical device, Multi-In-1 card reader), Game Keys, TouchPad & Mouse, Audio Features & Printer.
- Chapter 3 The computer's power management options.
- **Chapter 4** The installation of the **drivers** and utilities essential to the operation or improvement of some of the computer's subsystems.
- Chapter 5 An outline of the computer's built-in software or **BIOS** (Basic Input Output System).
- Chapter 6 Instructions for upgrading your computer.
- Chapter 7 A quick guide to the computer's RAID, PC Camera, Wireless LAN, Fingerprint and Bluetooth & WLAN Combo modules (some of which may be optional depending on your purchase configuration).
- Chapter 8 A troubleshooting guide.
- Appendix A Definitions of the interface, ports/jacks which allow your computer to communicate with external devices.
- Appendix B Information on the NVIDIA Video driver controls.
- Appendix C The computer's specification.

Quick Start Guide

Advanced Users

If you are an advanced user you may skip over most of this Quick Start Guide. However you may find it useful to refer to "*Drivers & Utilities*" on page 4 - 1, "BIOS Utilities" on page 5 - 1 and "Upgrading The Computer" on page 6 - 1 in the User's Manual. You may also find the notes marked with a \checkmark of interest to you.



Beginners and Not-So-Advanced Users

If you are new to computers (or do not have an advanced knowledge of them) then the information contained in this Quick Start Guide should be enough to get you up and running. Eventually you should try to look through all the documentation (more detailed descriptions of the functions, setup and system controls are covered in the remainder of the User's Manual), but do not worry if you do not understand everything the first time. Keep this manual nearby and refer to it to learn as you go. You may find it useful to refer to the notes marked with a \mathscr{P} as indicated in the margin. For a more detailed description of any of the interface ports and jacks see "Interface (Ports & Jacks)" on page A - 1.

Warning Boxes

No matter what your level please pay careful attention to the warning and safety information indicated by the the symbol. Also please note the safety and handling instructions as indicated in the *Preface*.

Not Included

Operating Systems (e.g. *Windows 7*) and applications (e.g. word processing, spreadsheet and database programs) have their own manuals, so please consult the appropriate manuals.

Drivers

If you are installing new system software, or are re-configuring your computer for a different system, you will need to install the appropriate drivers. Drivers are programs which act as an interface between the computer and a hardware component e.g. a wireless network module. It is very important that you install the drivers in the order listed in *Table 4 - 1, on page 4 - 3*. You will be unable to use most advanced controls until the necessary drivers and utilities are properly installed. If your system hasn't been properly configured (your service representative may have already done that for you), refer to "*Drivers & Utilities*" on page 4 - 1 for installation instructions.

Ports and Jacks

See "Ports and Jacks" on page A - 2 for a description of the interface (ports & jacks) which allow your computer to communicate with external devices, connect to the internet etc.

Quick Start Guide

System Software

Your computer may already come with system software pre-installed. Where this is not the case, or where you are re-configuring your computer for a different system, you will find the *Windows 7 (with Service Pack 1 installed)* operating system is supported.

Note: In order to run *Windows 7 (SP1)* without limitations or decreased performance, your computer requires a minimum **1GB** of system memory (RAM).

RAID & AHCI Setup

Note that setting up a RAID, or AHCI mode, needs to be done prior to installing the *Windows OS* (see "Setting Up SATA RAID or AHCI Mode" on page 7 - 2).

System Startup

- 1. Remove all packing materials, and place the computer on a stable surface.
- 2. Securely attach any peripherals you want to use with the notebook (e.g. keyboard and mouse) to their ports.
- 3. Attach the AC/DC adapter to the DC-In jack at the rear of the computer, then plug the AC power cord into an outlet, and connect the AC power cord to the AC/DC adapter.
- Use one hand to raise the lid/LCD to a comfortable viewing angle (it is preferable not to exceed 135 degrees); use the other hand (as illustrated in *Figure 1 - 1* below) to support the base of the computer (Note: Never lift the computer by the lid/LCD).
- 5. Raise the lid/LCD to a comfortable viewing angle, and press the power button.




Figure 1 - 1 - Computer with AC/DC Adapter Plugged-In/Opening the Lid/LCD

Quick Start Guide

Figure 1 - 2 LCD Panel Open & Top View

- 1. Optional Built-In PC Camera
- 2. LCD
- 3. LED Status Indicators
- 4. Touch Sensor Instant Keys
- 5. 8 * Gaming Keys
- 6. Keyboard
- TouchPad and Buttons
- 8. Fingerprint Reader Module (**optional**)
- 9. LED Power Indicators
- 10. LCD Panel Color LED

See *Appendix A* for a more detailed description of the ports & jacks etc.

System Map: LCD Panel Open & Top View



泛

Wireless Device Operation Aboard Aircraft

The use of any portable electronic transmission devices (e.g. WLAN or Bluetooth) aboard aircraft is usually prohibited. Make sure any wireless modules are OFF if you are using the computer aboard aircraft.

Use the appropriate function key combination/Touch Sensor Key to toggle power to any wireless modules, and check the indicators to see if any modules are powered on or not (see *Table 1 - 2*, on page 1 - 9).



LED Indicators

The two sets of LED indicators (**LED Status Indicators** and **LED Power Indicators**) display helpful information about the current status of the computer.

lcon	Color	Description	lcon	Color	Description
0	Blinking Blue	Hard Disk Activity		Orange	DC Power is Plugged In
	Blue	Number Lock is Activated		Green	The Computer is On
A	Blue	Caps Lock is Activated	Ð/U	Blinking Green	The Computer is In Sleep Mode
Ţ	Blue	Scroll Lock is Activated		Blinking Orange*	The Powered USB Port is On*
				Orange	The Battery is Charging
			(11	Blinking Orange	The Battery has Reached Critically Low Power Status
				Green	The Battery is Fully Charged

Table 1 - 1 - LED Status Indicators

*Note: The powered USB 2.0 port (see *Figure 1 - 7 on page 1 - 14*) may be toggled on /off by means of the $\mathbf{Fn} + \mathbf{Power}$ **Button** key combination. When the powered USB port is on it will supply power when the system is off but still powered by the AC/DC adapter plugged into a working outlet, or powered by the battery with a capacity level above 20% (this may not work with certain devices - see page 8 - 12).

Quick Start Guide

Game Keys

The eight **Game Keys** on the left of the computer allow macros to be configured for common keystrokes used in applications, as long as the driver is installed.

on	
73	8
-	•
-	REC
-	STOP
ОК	CANCEL
	73

Figure 1 - 3 - Game Key Configuration

Touch Sensor Instant Keys

Press the Touch Sensor Instant Keys on the computer to toggle the appropriate function on/off. When a module is powered on the appropriate icon will be highlighted.

lcon	Description	lcon	Description	
Ö	*Light Sensor Toggle	(((?)))	Wireless LAN Module Power Toggle	
Ó	PC Camera Module Power Toggle	S	Activate the Default Internet Browser	
*	Bluetooth Module Power Toggle	6	THX TruStudio Pro Toggle (see page 7 - 64)	
J.	**Silent Mode Toggle	Ŕ	Mute Toggle	
	- VOLUME +	Volume Control Slider (move your finger slowly along the slider to adjust the system volume)		

Table 1 - 2 - Touch Sensor Instant Keys

*When enabled, the **Light Sensor** will automatically adjust screen brightness according to the background environment.

When enabled, **Silent Mode will reduce fan noise and save power consumption. Note this may reduce computer performance.

Quick Start Guide

ß

Other Keyboards

If your keyboard is damaged or you just want to make a change, you can

use any standard USB

keyboard. The system will

detect and enable it automatically. However spe-

unique to the system's

regular keyboard may not

Num Lk & Scr Lk

Hold down the **Fn Key** and Scr Lk/Num Lk to en-

able scroll lock/number lock, and check the LED indicator for status.

cial

work.

functions/hot-keys

Keyboard

The keyboard has an embedded numerical keypad for easy numeric data input, and features function keys to allow you to change operational features instantly. See *Table 1 - 3, on page 1 - 11* for full function key combination details.



Figure 1 - 4 - Keyboard

Special Characters

Some software applications allow the number-keys to be used with **Alt** to produce special characters. These special characters can only be produced by using the numeric keypad. Regular number keys (in the upper row of the keyboard) will not work. Make sure that **NumLk** is on.

1

Function Keys & Visual Indicators

The **function keys** (F1 - F12 etc.) will act as **hot keys** when pressed while the **Fn** key is held down. In addition to the basic function key combinations; visual indicators (see the table below) are available when the Hot Key driver is installed (see "*Hot Key*" on page 4 - 7). After installing the driver an icon will appear in the taskbar.

Keys	Function/Visual Indicators		Keys	Function/Visual Indicators	
Fn + ~	Play/Pause (in Audio/Video Programs)		Fn + F8/F9	Brightness Decrease/Increase	
Fn + F1	Touchpad Toggle		Fn + F10	PC Camera Power Toggle	
Fn + F2	Turn LCD Backlight Off (Press a key to or use Touchpad to turn on)		Fn + F11	WLAN Module Power Toggle	
Fn + F3	Mute Toggle		Fn + F12	Bluetooth Module Power Toggle	
Fn + F4	Sleep Toggle		Fn + NumLk	Number Lock Toggle	
Fn + F5/F6	Volume Decrease/ Increase		Fn + ScrLk	Scroll Lock Toggle	
Fn + F7	Display Toggle Note: DO NOT use the Fn + F7 key combination to toggle through display options when SLI is enabled (see "SLI Multi GPU Configuration" on page B - 14).		Fn + Power Button	Powered USB 2.0 Port Power Toggle	

Table 1 - 3 - Function Keys & Visual Indicators

Quick Start Guide

Figure 1 - 5 Front View

- 1. Speakers
- 2. LED Power Indicators
- 3. DC-In Jack

See *Appendix A* for a more detailed description of the ports & jacks etc.

System Map: Front & Rear Views





1 - 12 System Map: Front & Rear Views

- (1

System Map: Right View



USB Ports

Note that the connections to the USB ports only fit one way, do not force them.

Ø

ExpressCard Slot

The ExpressCard Slot accepts either ExpressCard/34 or ExpressCard/54 formats.

Figure 1 - 6 Right View

- 1. Express Card Slot
- 2. Headphone-In Jack
- 3. Microphone-In Jack
- 4. Line-In Jack
- 5. S/PDIF-Out Jack
- 6. Combined eSATA/ USB Port
- 7. USB 2.0 Port
- 8. Security Lock Slot
- 9. Power Button

See *Appendix A* for a more detailed description of the ports & jacks etc.

Figure 1 - 7 Left View

- 1. DVI-Out Port
- 2. USB 2.0 Port
- 3. USB 2.0 Port (Powered)
- 4. RJ-45 LAN Jack
- 5. HDMI-Out Port
- 6. Multi-In-1 Card Reader
- 7. 2 * USB 3.0 Ports
- 8. Mini-IEEE 1394a Port
- 9. Optical Device Drive Bay

See *Appendix A* for a more detailed description of the ports & jacks etc.

Mini-IEEE 1394a Port The Mini-IEEE 1394 port only supports SELF POW-ERED IEEE 1394 devices.

ß

System Map: Left View



// Multi-in-1 Card Reader

The card reader allows you to use the most popular digital storage card formats:

MMC (MultiMedia Card) / RSMMC SD (Secure Digital) / Mini SD / SDHC / SDXC MS (Memory Stick) / MS Pro / MS Duo

HDMI Port

Note that the HDMI Port supports video and audio signals to attached external displays (also see "HD-MI Audio Configuration" on page B - 18). Note that THX TruStudio Pro will be disabled when you are connecting to an external display through an HDMI connection (see page 7 - 110).

USB 3.0 Ports & USB Port Power

USB 3.0 ports are denoted by their blue color; USB 2.0 ports are colored black. Note that the USB 3.0 port requires a driver installation (see *"USB 3.0" on page 4 - 7*) and is not operational under DOS. The powered USB 2.0 port 3 can supply power when the system is off but still powered by the AC/ DC adapter plugged into a working outlet, or powered by the battery with a capacity level above 20% (this may not work with certain devices - see page 8 - 12). Toggle power to this port by using **Fn + power button**.

泛

Disk Eject Warning

Don't try to eject a CD/DVD while the system is accessing it. This may cause the system to "crash". Stop the disk first then eject it, or press the stop button twice.

CD/DVD Emergency Eject

If you need to manually eject a CD/DVD (e.g. due to an unexpected power interruption) you may push the end of a straightened paper clip into the emergency eject hole. Do not use a sharpened pencil or any object that may break and become lodged in the hole. Don't try to remove a floppy disk/CD/DVD while the system is accessing it. This may cause the system to "crash".

Changing DVD Regional Codes

O

Go to the **Control Panel** and double-click **Device Manager (Hardware and Sound)**, then click the **+** next to **DVD/CD-ROM drives**. Double-click on the DVD-ROM device to bring up the **Properties** dialog box, and select the **DVD Region** (tab) to bring up the control panel to allow you to adjust the regional code.

DVD region detection is device dependent, not OSdependent. You can select your module's region code **5** times. The fifth selection is permanent. This cannot be altered even if you change your operating system or you use the module in another computer.

Figure 1 - 8 Bottom View

- 1. Sub Woofer
- 2. Fan Outlet/Intake
- 3. Component Bay Cover
- 4. Battery
- 5. HDD Bay

System Map: Bottom View



Overheating


To prevent your computer from overheating make sure nothing blocks the vent(s)/fan intake(s) while the computer is in use.

Battery Information

Always completely discharge, then fully charge, a new battery before using it. Completely discharge and charge the battery at least once every 30 days or after about 20 partial discharges. See *"Battery Information" on page 3 - 10* for full instructions.

Windows 7 Start Menu & Control Panel

Most of the control panels, utilities and programs within *Windows 7* (and most other *Windows* versions) are accessed from the **Start** menu. When you install programs and utilities they will be installed on your hard disk drive, and a shortcut will usually be placed in the **Start** menu and/or the desktop. Right-click the **Start menu** icon , and then select **Properties** if you want to customize the appearance of the **Start** menu.



In many instances throughout this manual you will see an instruction to open the **Control Panel**. The **Control Panel** is accessed from the **Start** menu, and it allows you to configure the settings for most of the key features in *Windows* (e.g. power, video, network, audio etc.). *Windows* 7 provides basic controls for many of the features, however many new controls are added (or existing ones are enhanced) when you install the drivers. To see all controls it may be necessary to toggle off *Category View* to view the control panel icons.

Video Features

You can switch display devices, and configure display options, from the **Display** control panel (in **Appearances** and **Personalization**) in *Windows* 7 (see over). For more detailed video information see "*NVIDIA Video Driver Controls*" *on page B* - 1.

To access Display (Control Panel) and Screen Resolution in Windows:

- 1. Click Start and click Control Panel.
- 2. Click Display (icon) In the Appearances and Personalization category.
- 3. Click Adjust Screen Resolution/Adjust resolution.

OR

- 4. Alternatively you can right-click the desktop and select Screen resolution (1) (*Figure 1 10 on page 1 19*).
- 5. Use the dropbox to select the screen Resolution (2) (Figure 1 10 on page 1 19).



Screen Resolution



Note that card types, specifications and drivers are subject to continual updates and changes. Check with your service center for the latest details on video cards supported.

	View	۲
	Sort by	+
	Refresh	
	Paste	
	Paste shortcut	
1	NVIDIA Control Panel	
	New 1	×
	Screen resolution	>
	Gadgets	_
2	Personalize	

Change the	appearance of your display	
		Dete <u>c</u> t Identify
Di <u>s</u> play:	1. Mobile PC Display 💌	
Resolution:	1920 × 1080 (recommended)	
Orientation:	Landscape 👻	
		Advanced setting
Connect to a pr	ojector (or press the 🚑 key and tap P)	
Make text and o	ther items larger or smaller	
What display se	tings should I choose?	
		OK Cancel Apply



NVIDIA Control Panel

You can access the NVIDIA Control Panel as follows:

- 1. Click Start, and click Control Panel.
- 2. Click NVIDIA Control Panel () (Figure 1 11) In the Appearances and Personalization category.
- See "NVIDIA Video Driver Controls" on page B 1 for full details on control panels etc. OR
- 4. You can also access the control panel by right-clicking the desktop and selecting NVIDIA Control Panel (2).




Figure 1 - 11 - NVIDIA Control Panel

Power Options

The **Power Options** (**Hardware and Sound** menu) control panel icon in *Windows* (see page *1 - 17*) allows you to configure power management features for your computer. You can conserve power by means of **power plans** and configure the options for the **power button**, **sleep button**, **computer lid** (**when closed**), **display** and **sleep** mode from the left menu. Note that the **Power saver** plan may have an affect on computer performance.

Click to select one of the existing plans, or click *Create a power plan* in the left menu and select the options to create a new plan. Click *Change plan settings* and click *Change advanced power settings* to access further configuration options.

Pay attention to the instructions on battery care in "Battery Information" on page 3 - 10.




Figure 1 - 12 - Power Options



Chapter 2: Storage Devices, Mouse, Audio & Printer

Overview

Read this chapter to learn more about the following main features and components of the computer:

- Hard Disk Drive
- Optical Device
- Multi-In-1 Card Reader
- ExpressCard Slot
- Game Keys
- Audio Features
- TouchPad and Buttons/Mouse
- Adding a Printer

Storage Devices, Mouse, Audio & Printer



沃 **Power Safety**

Before attempting to access any of the internal computer please ensure that the machine is not connected to the AC power, and that the machine is turned off. Also ensure that all peripherphone lines, are disconnected from the comput-

> *Figure 2 - 1* Hard Disk Bay

Hard Disk Drive

The hard disk drive(s) is(are) used to store your data in the computer. The hard disk(s) can be taken out to accommodate other 2.5" serial (SATA) hard disk drives with a height of 9.5 mm. The hard disk bay (1) is accessible from the bottom of your computer as seen below.

The computer can accommodate up to three hard disks (two in the primary bay, and one under the optical device), and these may be configured in RAID, AHCI or IDE modes. Further details on removing and inserting the hard disk are available in "Upgrading the Hard Disk Drive(s)" on page 6 - 5.




Optical Device

There is a bay for a 5.25" optical (CD/DVD) device (12.7mm height). The actual device will depend on the model you purchased (see "Storage" on page C - 2). The optical device is usually labeled "Drive D:" and may be used as a boot device if properly set in the **BIOS** (see "Boot Menu" on page 5 - 12).

Loading Discs

To insert a CD/DVD, press the open button 1 and carefully place a CD/DVD onto the disc tray with label-side facing up (use just enough force for the disc to click onto the tray's spindle). Gently push the CD/DVD tray in until its lock "clicks" and you are ready to start. The busy indicator 2 will light up while data is being accessed, or while an audio/video CD, or DVD, is playing. If power is unexpectedly interrupted, insert an object such as a straightened paper clip into the emergency eject hole 3 to open the tray.



Sound Volume Adjustment

How high the sound volume can be set depends on the setting of the volume control within Windows. Click the Volume icon on the taskbar to check the setting.

Peripherals must be connected before you turn on the system.

> *Figure 2 - 2* **Optical Device**



Storage Devices, Mouse, Audio & Printer





CD Emergency Eject

If you need to manually eject a CD (e.g. due to an unexpected power interruption) you may push the end of a straightened paper clip into the emergency eject hole. However please do NOT use a sharpened pencil or similar object that may break and become lodged in the hole.

Disk Eject Warning

Don't try to remove a CD/DVD while the system is accessing it. This may cause the system to "crash".

Handling CDs or DVDs

Proper handling of your CDs/DVDs will prevent them from being damaged. Please follow the advice below to make sure that the data stored on your CDs/DVDs can be accessed.

Note the following:

- Hold the CD or DVD by the edges; do not touch the surface of the disc.
- Use a clean, soft, dry cloth to remove dust or fingerprints.
- Do not write on the surface with a pen.
- Do not attach paper or other materials to the surface of the disc.
- Do not store or place the CD or DVD in high-temperature areas.
- Do not use benzene, thinner, or other cleaners to clean the CD or DVD.
- Do not bend the CD or DVD.
- Do not drop or subject the CD or DVD to shock.

DVD Regional Codes

To change the DVD regional codes see "Changing DVD Regional Codes" on page 1 - 15.

	DVD Regional Coding				
Region	Geographical Location	General DVD Region Volumes Driver Details			
1	USA, Canada	Most DVDs are encoded for play in specific regions. To play a regionalized DVD on your computer, you must set your DVD drive to play discs from that region by selecting a geographic area from the			
2	Western Europe, Japan, South Africa, Middle East & Egypt	following list. CAUTION You can change the region a limited number of times. After Changes remaining reaches zero, you cannot change the region even if you reinstall Windows or move your DVD drive to a different computer.			
3	South-East Asia, Taiwan, South Korea, The Philippines, Indonesia, Hong Kong	Ohanges remaining: 5 To change the current region, select a geographic area, and then click OK. United Arab Emirates United Kingdom United Kingdom			
4	South & Central America, Mexico, Australia, New Zealand	Uruguay Utabékistan Vanuatu Vatican City Current Region: Not Selected			
5	N Korea, Russia, Eastern Europe, India & Most of Africa	New Region: Region 1			
6	China				

Table 2 - 1DVD Regional Coding

Storage Devices, Mouse, Audio & Printer

Card Reader Cover

ß

Make sure you keep the cover in the card reader when not in use. This will help prevent foreign objects and/or dust getting in to the card reader.

Figure 2 - 3 **Right View**

Card Reader 1

Multi-In-1 Card Reader

The card reader allows you to use some of the latest digital storage cards. Push the card into the slot and it will appear as a removable device, and can be accessed in the same way as your hard disk (s). Make sure you install the Card Reader driver (see "Card Reader" on page 4 - 7).

- MMC (MultiMedia Card) / RSMMC
- SD (Secure Digital) / Mini SD / SDHC / SDXC
- MS (Memory Stick) / MS Pro / MS Duo

PC adapters may be required for some of these cards and are usually supplied with them.



ExpressCard Slot

The computer is equipped with an **ExpressCard/34/54** slot that reads Express Card/ 34 and ExpressCard/54 formats. ExpressCards are the successors to PCMCIA (PC Cards).

ExpressCard/54 is used for applications which require a larger interface slot, e.g. CompactFlash card reader. The number denotes the card width; 54mm for the Express Card/54 and 34mm for the ExpressCard/34. Make sure you install the ExpressCard driver (see "*Card Reader/ExpressCard*" *on page 4 - 6*).

Inserting and Removing ExpressCards

- Align the ExpressCard with the slot and push it in until it locks into place.
- To remove an ExpressCard, simply press the card to eject it.



Figure 2 - 4 Express Card Slot

Game Keys

The eight game hot keys on the left of the computer allow macros to be configured for common keystrokes used in applications (the keys can assigned macros for any program, not only games). To configure the keys follow the instructions below (make sure you have installed the **GameKey** Utility driver - see "GameKey Utility" on page 4 - 7).

- 1. Run the **Game Key Configuration** program from the desktop icon 😥 (or from C:\Program Files\Chicony\GameKeys\GmKeyCfgUtl.exe).
- 2. Double-click the button 👰 for the appropriate key (it will turn red 🕘).
- 3. When the button is red 🕘 you may then record the keystrokes to be assigned to the Game Key.

Figure 2 - 5 Game Key Configuration

5	6	7	8
Shift press W press W release Shift relea			REC STOP
APP	ny I	ОК	CANCE

- 4. Click OK.
- 5. Repeat the procedure for the other Game Key if required.
- 6. Close the Game Key Configuration window.
- 7. The keystroke order will be repeated with the appropriate button press in any application program.


Audio Features

You can configure the audio options on your computer from the **Sound** $\overset{@}{=}$ control panel in *Windows*, or from the **Realtek HD Audio Manager** $\overset{@}{=}$ icon in the notification area/control panel (right-click the notification area icon $\overset{@}{=}$ to bring up an audio menu). The volume may also be adjusted by means of the **Fn** + **F5/F6** key combination (see *Table 1 - 3, on page 1 - 11*).



See *"HDMI Audio Configuration" on page B - 18* for a description of the audio configuration when connecting an HDMI supported display device.

See *"THX TruStudio Pro Audio" on page 7 - 64* for more information on the THX TruStudio Pro Audio setup.



B

The sound volume level is set using the volume control within **Windows** (and the volume function keys on the computer). Click the volume icon in the notification area to check the setting.

Headphone Configuration

It is recommended that you set the **Speaker Configuration** to **Stereo** (not to 5.1 or 7.1 Speaker) when listening through headphones in order to maximize audio quality.

> Figure 2 - 6 Realtek Audio Manager

Setup for Audio Recording

To record audio sources on your computer at optimum quality follow the instructions below:

- 1. Click **Start**, and click **Control Panel** (or point to **Settings** and click **Control Panel**) and make sure you are in **Classic View**.
- 2. Click **Realtek HD Audio Manager** (or right-click the notification area icon and select **Sound Manager**).
- 3. Click **Microphone Effects** (tab) in **Microphone** (tab), and then click to select **Noise Suppression** (button), or adjust the **Recording Volume** level to around **60**, to obtain the optimum recording quality.
- 4. Click **OK** to close the control panel and save the settings.



Figure 2 - 7 Realtek Audio Manager -Recording Setup

Suppressing Audio Background Noise

A background noise may occur when audio power management is enabled, and the system resumes from power saving. To solve this problem you can disable Realtek HD Audio Manager Power Management.

- 1. Click **Start**, and click **Control Panel** (or point to **Settings** and click **Control Panel**) and make sure you are in **Classic View**.
- 2. Click **Realtek HD Audio Manager** (or right-click the taskbar icon **and select Sound Manager**).
- 3. Click the **Power Management** icon **m**.





- 4. Make sure that **Power Management** is **disabled** (when disabled the icon will be black (); when enabled the icon will be blue ()).
- 5. Click **OK** to save the setting and close the control panel.




Figure 2 - 9 **Realtek Audio Manager Power Management**

Setup for 5.1 or 7.1 Surround Sound

To setup your system for 5.1 or 7.1 surround sound you will need to connect the audio cables to the Headphone-Out, Line-In, Microphone-In jack and S/PDIF-Out jacks (*note: the S/PDIF jack is used for 7.1 surround sound only*).

- 1. Click Start, and click Control Panel (or point to Settings and click Control Panel) and make sure you are in Classic View.
- 2. Click **Realtek HD Audio Manager** (or right-click the notification area icon and select **Sound Manager**).
- 3. Click Speakers (tab) and click Speaker Configuration (tab).
- 4. Select **5.1 or 7.1 Speaker** from the **Speaker Configuration** pull-down menu.





Auto Popup Dialog

You should enable the auto popup dialog to automatically detect when a device has been plugged-in. If disabled, double-click **connector settings** and click the box to enable the auto popup detection of plugged-in devices.

泛

THX Audio & HDMI

Note that the THX audio effects do not apply to audio generated through an HDMI connection (see page 7 -67).

Press the THX TruStudio Pro Touch Sensor Instant Key d to toggle the THX TruStudio AP On/Off.

Figure 2 - 10 Speaker Configuration (7.1)

- 5. Plug the front speaker cables into the Headphone-Out Jack.
- 6. Plug in the other cables (you may require an adapter to connect each cable to the appropriate jack e.g a stereo mini to dual RCA adapter) from your speakers as follows:
- Line-In Jack = Rear Speaker Out
- Microphone-In Jack = Center/Subwoofer Speaker Out
- S/PDIF-Out Jack = Side Speaker Out (for 7.1 Surround Sound Only)
- As you plug in each cable a dialog box will pop up (see "Auto Popup Dialog" on page 2 - 13).
- 8. Click to put a tick in the appropriate box according to the speaker plugged-in (e.g. Rear Speaker Out), and then click **OK** to save the setting.
- 9. Click OK to exit Realtek HD Audio Manager.

The current connected device is :	The current connected device is :	The current connected device is :
Which device did you plug in?	Which device did you plug in?	Which device did you plug in?
Enable auto popup dialog, when device has been plugged in OK	Enable auto popup dialog, when device has been plugged in	☑ Enable auto popup dialog, when device has been plugged in OK

Note: Side Speaker Out is required for 7.1 Surround only.

Figure 2 - 11 Connected Device Auto Popup

TouchPad and Buttons/Mouse

The TouchPad is an alternative to the mouse; however, you can also add a mouse to your computer through one of the USB ports. The TouchPad buttons function in much the same way as a two-button mouse.

Once you have installed the TouchPad driver (see "*TouchPad*" on page 4 - 7) you can configure the functions from the Mouse control panel in *Windows*, or by doubleclicking the TouchPad driver icon \square on the **taskbar**. You may then configure the TouchPad tapping, buttons, scrolling, pointer motion and sensitivity options to your preferences. Use the **Fn** + **F1** key combination to toggle the TouchPad on/off.

Buttons Pointers Pointers Optime Control of Content Control of Content Con	Buttons Pointers Pointer Options Wheel Hardware Image: Optional state Vertical Scrolling Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional state Image: Optional
ClickLock	
Tum on ClickLock	
Enables you to highlight or drag without holding down the mouse button. To set, briefly press the mouse button. To release, click the mouse button again.	
OK Cancel Apply	OK Cancel Acc

CP TouchPad Scrolling

This computer model series may feature different TouchPad versions.

These TouchPads may differ in their vertical scrolling function in most scrollable windows.

Some TouchPads require sliding the finger up and down on the right of the TouchPad to scroll the window. Other versions require tapping/holding down the finger at the top right or bottom right of the TouchPad to scroll the window.

Figure 2 - 12 **Mouse Properties**

Storage Devices, Mouse, Audio & Printer

2



Show Video

You can get a clearer view of the gestures involved by clicking the **Show Video** option for each gesture item.

Select the gesture (Pinch Zoom, Rotating, Three Fingers Down and Three Finger Flick) in the Device Settings > Settings left tree menu and click the Show Video button to see the demonstration video.

For more details on any of the gestures see the **help** in the lower part of the right menu window.


Figure 2 - 13 Mouse Properties -Device Settings

Gestures and Device Settings

The Synaptics Gestures Suite application allows you to use a specific gesture (action) on the surface of the Touchpad to perform specific actions to manipulate documents, objects and applications.

You can configure the settings from the Device Settings tab in Mouse Properties:

- 1. Click Start, and click Control Panel (or point to Settings and click Control Panel).
- 2. Click Mouse (Hardware and Sound).
- 3. Click Device Settings (tab) and click Settings.
- 4. Use the menu tree on the left to access the user configurable settings.



Scrolling

The Two-Finger scrolling feature works in most scrollable windows and allows you to scroll horizontally and vertically. Place two fingers, slightly separated, on the TouchPad surface and slide both fingers in the direction required (in a straight continuous motion).



Zooming

The Pinch Zoom gesture can be used to perform the same function as a scroll wheel in *Windows* applications that support CTRL + scroll wheel zoom functionality. Place two fingers on the TouchPad (for best results use the tips of the fingers) and slide them apart to zoom in, or closer together to zoom out.



Figure 2 - 14 Scrolling Gesture

Mouse Driver

If you are using an external mouse your operating system may be able to auto-configure your mouse during its installation or only enable its basic functions. Be sure to check the device's user documentation for details.

Figure 2 - 15 **Zooming Gesture**

Storage Devices, Mouse, Audio & Printer

Rotating


Use the Pivot Rotate gesture to rotate objects (e.g. photos) in 90 degree increments. Place a finger down on the left "target" zone and keep it stationary. Place another finger near the middle of the TouchPad and slide it in a circular motion around the stationary finger (clockwise or counterclockwise) to rotate the object.

Figure 2 - 16 **Rotating Gesture**



The Three Finger-Flick gesture may be used to enhance navigation with a variety of applications such as browsing the Internet or scrolling through a photo viewer. The Three Fingers Down gesture may be used to launch user-selectable applications.

Figure 2 - 17 Flick/Press Gesture





Adding a Printer

The most commonly used peripheral is a printer. The following conventions will help you to add a printer; however it is always best to refer to the printer manual for specific instructions and configuration options.

USB Printer

Most new printers have a USB interface connection. You may use any one of the ports to connect the printer.

Install Instructions:

- 1. Set up the printer according to its instructions (unpacking, paper tray, toner/ink cartridge etc.).
- 2. Turn ON the computer.
- 3. Turn ON the printer.
- 4. Connect the printer's USB cable to one of the USB ports on the computer.
- 5. *Windows* will identify the printer and either load one of its own drivers or ask you to supply one. Follow the on-screen instructions.

Parallel Printer

This is still a very common type of printer. The install instructions are in the sidebar (you will need to purchase a parallel to USB converter).

Parallel Printer

After setting up the printer attach the parallel cable to the printer.

Connect the printer's parallel cable to the Parallel to USB converter, and then plug the converter into the USB port.

Turn ON the printer, then turn ON the computer.

Windows will identify the printer and either load one of its own drivers or ask you to supply one. Follow the on-screen instructions.

2

Overview 3 - 1

Chapter 3: Power Management

Overview

To conserve power, especially when using the battery, your computer power management conserves power by controlling individual components of the computer (the LCD and hard disk drive) or the whole system.

This chapter covers:

- The Power Sources
- Turning On the Computer
- Power Plans
- Power-Saving States
- Configuring the Power Buttons
- Battery Information

The computer uses enhanced power saving techniques to give the operating system (OS) direct control over the power and thermal states of devices and processors. For example, this enables the OS to set devices into low-power states based on user settings and information from applications.

OS Note

Power management functions will vary slightly depending on your operating system. For more information it is best to refer to the user's manual of your operating system.

(Note: All pictures used on the following pages are from the *Windows* 7 OS.)

The Power Sources

The computer can be powered by either an AC/DC adapter or a battery pack.

AC/DC Adapter

Use only the AC/DC adapter that comes with your computer. The wrong type of AC/DC adapter will damage the computer and its components (see page C - 4).

- 1. Attach the AC/DC adapter to the DC-In jack at the rear of the computer.
- 2. Plug the AC power cord into an outlet, and then connect the AC power cord to the AC/DC adapter.
- 3. Raise the lid/LCD to a comfortable viewing angle.
- 4. Press the power button to turn "On".

Battery

The battery allows you to use your computer while you are on the road or when an electrical outlet is unavailable. Battery life varies depending on the applications and the configuration you're using. To increase battery life, let the battery discharge completely before recharging (see "How do I completely discharge the battery?" on page 3 - 14).

We recommend that you do not remove the battery. For more information on the battery, please refer to "*Battery Information*" on page 3 - 10.

Turning On the Computer

Now you are ready to begin using your computer. To turn it on simply press the power button on the front panel.

When the computer is on, you can use the power button as a Stand by/Hibernate/ Shutdown hot-key button when it is pressed for less than **4 seconds** (pressing and holding the power button for longer than this will shut the computer down). Use **Power Options** in the *Windows* control panel to configure this feature.



Forced Off

If the system "hangs", and the **Ctrl + Alt + Del** key combination doesn't work, press the power button for **4 seconds**, or longer, to force the system to turn itself off.

Power Button as Stand by or Hibernate Button

You can use the OS's **Power Options** control panel to set the power button to send the system into Stand by or Hibernate mode (see your OS's documentation, or *"Configuring the Power Buttons" on page 3* - 8 for details).

Power Management

Resuming Operation

ß

See **Table 3 - 1**, **on page 3 - 9** for information on how to resume from a power-saving state.

Password

It is recommended that you enable a password on system resume in order to protect your data.

Figure 3 - 1 Power Plan Advanced Settings (Win 7)

Power Plans

The computer can be configured to conserve power by means of **power plans**. You can use (or modify) an existing **power plan**, or create a new one.

The settings may be adjusted to set the **display** to turn off after a specified time, and to send the computer into **Sleep** after a period of inactivity.

Click *Change plan settings* and then click *Change advanced power settings* to access further configuration options in **Advanced Settings**.

Change settings for the Choose the sleep and display se			uter to use.		Select the power plan that you want to then choose settings that reflect how y	
	On ba	ittery	Plugged in		computer to manage power.	
Dim the display:	2 minutes	•	5 minutes •		Balanced (Active)	
Turn off the display:	5 minutes	•	10 minutes 🔹		⊟ Balanced	
Put the computer to sleep:	15 minutes	•	30 minutes 🔹		E Require a password on wakeup	
Adjust plan brightness:	•	- 14	o0 &		On battery: Yes * Plugged in: Yes	
					⊞ Hard disk	
ghange advanced power setting	\rightarrow				Desktop background settings Wireless Adapter Settings	
Restore detault settings for this	plan					
			Swe durges	Cancel	B Power buttons and lid	
					Restore p	olan defaul

Each *Windows* **power plan** will also adjust the processor performance of your machine in order to save power. This is worth bearing in mind if you are experiencing any reduced performance (especially under DC/battery power).

Choose **High performance** (you may need to click **Show additional plans** to view the High performance plan) for maximum performance when the computer is powered from an AC power source. Choose the **Power saver** (bear in mind that this scheme may slow down the overall performance of the computer in order to save power) for maximum power saving when the computer is battery (DC power) powered.




Figure 3 - 2 Power Plans (Win 7)

Power Management

Power-Saving States

You can use power-saving states to stop the computer's operation and restart where you left off. *Win* **7** uses the **Sleep, Hibernate** and **Shut Down** power-saving states.

Sleep

In **Sleep** all of your work, settings and preferences are saved to memory before the system sleeps. When you are not using your computer for a certain length of time, which you specify in the operating system, it will enter **Sleep** to save power.

The PC wakes from **Sleep within seconds** and will return you to where you last left off (what was on your desktop) without reopening the application(s) and file(s) you last used.

If your mobile PC in **Sleep** is running on battery power the system will use only a minimum amount of power. After an extended period the system will save all the information to the hard disk and shut the computer down before the battery becomes depleted.

Hibernate

Hibernate uses the least amount of power of all the power-saving states and saves all of your information on a part of the hard disk before it turns the system off. If a power failure occurs the system can restore your work from the hard disk; if a power failure occurs when work is saved only to memory, then the work will be lost. **Hibernate** will also return you to where you last left off within seconds. You should put your mobile PC into **Hibernate** if you will not use the computer for a period of time, and will not have the chance to charge the battery.

Shut down

You should **Shut down** the computer if you plan to install new hardware (don't forget to remove the battery and follow all the safety instructions in **Chapter 6**), plan to be away from the computer for several days, or you do not need it to wake up and run a scheduled task. Returning to full operation from **Shut down** takes longer than from **Sleep** or **Hibernate**.



Silent Mode

You can use **Silent Mode** to reduce power consumption and fan noise. Use the **Silent Mode** Touch Sensor Instant Key *I* to toggle this mode on/off.

On screen visual indicators and the Touch Sensor Instant Key will display the **Silent Mode** status (see **Table 1 - 2, on page 1 - 9**).

Note **Silent Mode** may reduce computer performance.

Figure 3 - 3 **Start Menu Power**

Power Management

ß

Password Protection

It is recommended that you enable a password on wake up in order to protect your data.

However you can disable this setting from the **Power Options** menu by clicking **Require a password on wakeup** in the left menu, and selecting the options (click **Change settings that are currently unavailable**).

> *Figure 3 - 4* Power Options Define Power Buttons

Configuring the Power Buttons

The power/sleep button (Fn + F4 key combo) and closed lid may be set to send the computer in to a power-saving state. Click **Choose what the power buttons do** on the left menu in **Power Options** to bring up the menu.

and a state of the			
efine power buttons and turn o	n password protection	on	
noose the power settings that you want fo	r your computer. The chang	ges you make to the set	ttings on this
age apply to all of your power plans.			
ower and sleep buttons and lid settings			
	10		
	On battery	Plugg	ged in
0		-	
When I press the power button:	Sleep	Sleep	•
	Do nothing		
When I press the sleep button:	Sleep	Sleep	-
•	Hibernate Shut down	pare-t-	
When I close the lid:	Sleep	▼ Sleep	-
	Dicep	Siccp	
assword protection on wakeup			
Change settings that are currently unava	ailable		
(Require a password (recommended)			
When your computer wakes from slee	p. no one can access your	data without entering t	he correct
password to unlock the computer. Cre			
Don't require a password			
When your computer wakes from slee	p, anyone can access your	data because the comp	outer isn't
locked.			

ß

Closing the Lid If you have chosen to send the computer to Sleep when the lid is closed, raising the lid will wake the system up.

Resuming Operation

You can resume operation from power-saving states by pressing the power button, or in some cases pressing the sleep button (Fn + F4 key combo).

Power Status	lcon _{Đ-/ᠿ} Color	To Resume	
Power Off	Off	Press the Power Button	
Sleep Diplying Creen	Blinking Green	Press the Power Button	
Sleep	Billiking Green	Press the Sleep Button (Fn + F4 Key Combo)	
Hibernate	Off (battery)	Press the Power Button	
Tibernate	Orange (AC/DC adapter)		
Display Turned Off	Green	Press a Key or Move the Mouse/Touchpad	

Table 3 - 1 Resuming Operation

ß

Power Button

When the computer is on, you can use the power button as a Sleep/Hibernate/Shut Down hot key button when it is pressed for less than 4 seconds (pressing and holding the power button for longer than this will force the computer to shut down).

Power Management



When the battery is critically low, immediately connect the AC/DC adapter to the computer or save your work, otherwise, the unsaved data will be lost when the power is depleted.


Battery Information


Follow these simple guidelines to get the best use out of your battery.

Battery Power

Your computer's battery power is dependent upon many factors, including the programs you are running, and peripheral devices attached. You can set actions to be taken (e.g. Shut down, Hibernate etc.), and set critical and low battery levels from power plan **Change plan settings > Change advanced power settings** (see *Figure 3 - 1 on page 3 - 4*).

Click the battery icon **D** in the taskbar to see the current battery level and charge status.





3 - 10 Battery Information

Conserving Battery Power

- Use a **power plan** that conserves power (e.g **Power saver**), however note that this may have an affect on computer performance.
- Lower the brightness level of the LCD display. The system will decrease LCD brightness slightly to save power when it is not powered by the AC/DC adapter.
- Reduce the amount of time before the display is turned off.
- Close wireless, Bluetooth, modem or communication applications when they are not being used.
- Disconnect/remove any unnecessary external devices e.g. USB devices, ExpressCards etc.





Figure 3 - 6 Windows Mobility Center

Battery Life

Battery life may be shortened through improper maintenance. To optimize the life and improve its performance, fully discharge and recharge the battery at least once every 30 days.

We recommend that you do not remove the battery yourself. If you do need to remove the battery for any reason (e.g. long term storage) see "*Removing the Battery*" *on page 6 - 3*.

New Battery

Always completely discharge, then fully charge, a new battery (see "*Battery FAQ*" *on page 3 - 14* for instructions on how to do this).

Recharging the Battery with the AC/DC Adapter

The battery pack automatically recharges when the AC/DC adapter is attached and plugged into an electrical outlet. If the computer is powered on, and in use, it will take several hours to fully recharge the battery. When the computer is turned off but plugged into an electrical outlet, battery charge time is less. (Refer to "*LED Indicators*" on page 1 - 7 for information on the battery charge status, and to "*Battery Information*" on page 3 - 10 for more information on how to maintain and properly recharge the battery pack.)

Proper handling of the Battery Pack

- DO NOT disassemble the battery pack under any circumstances.
- DO NOT expose the battery to fire or high temperatures, it may explode.
- DO NOT connect the metal terminals (+, -) to each other.

泛

Damaged Battery Warning

Should you notice any physical defects (e.g. the battery is bent out of shape after being dropped), or any unusual smells emanating from the notebook battery, shut your computer down immediately and contact your service center. If the battery has been dropped we do not recommend using it any further, as even if the computer continues to work with a damaged battery in place, it may cause circuit damage, which may possibly result in fire. It is recommended that you replace your computer battery every two years.

Caution

Danger of explosion if battery is incorrectly replaced.


Replace only with the same or equivalent type recommended by the manufacturer. Discard used battery according to the manufacturer's instructions.


Battery FAQ

How do I completely discharge the battery?

Use the computer with battery power until it shuts down due to a low battery. Don't turn off the computer even if a message indicates the battery is critically low, just let the computer use up all of the battery power and shut down on its own.

- 1. Save and close all files and applications.
- 2. Create a power plan for discharging the battery and set all the options to Never.





3

3. Click *Change plan settings* (after creating it) and click *Change plan settings* > *Change advanced power settings*.

All Control Panel 1	tems Power Options	Search Control Parel
Control Panel Home	Select a power plan	
Require a password on wakeup	Power plans can help you maxin	mize your computer's performance or conserve
Choose what the power	energy. Make a plan active by s changing its power settings. Tel	electing it, or choose a plan and customize it by time more about power plans
buttons do Choose what closing the lid	Plans shown on the battery met	er
does	Discharge Battery	Change plan settings
Create a power plan	Power saver	
Choose when to turn off the display		Change plan settings your computer's performance where possible.
Change when the computer		
sleeps	Hide additional plans	
	Balanced (recommender Automatically balances pression)	Change plan settings enformance with energy consumption on
	capable hardware.	
	High performance	Change plan settings
	Favors performance, but r	nay use more energy.
-		
See also Personalization		
Windows Mobility Center		
User Accounts	Screen brightness	0 0 3
Change se Coore te s O Dimbre S fanette S Antere	Never Cystow • 1 Kitt Ruis Settings Httings for the plan: Discharge Battery terp and discling still you weit your comput Distance display: Never	
Change se Coore te s O Dimbre S fanette S Antere	New Option + Left has Setting Hittigs for the plan Discharge Battery was all blaive entry for your war you compu- discove New New New New New New New New New Ne	er to yet.
Change se Coore te s O Dimbre S fanette S Antere	New Option + Left has Setting Hittigs for the plan Discharge Battery was all blaive entry for your war you compu- discove New New New New New New New New New Ne	A Control
Change se Coore te s O Dimbre S fanette S Antere	New Option + Left has Setting Hittigs for the plan Discharge Battery was all blaive entry for your war you compu- discove New New New New New New New New New Ne	A Construction Construction Construction

Figure 3 - 8 Change Plan Settings / Change Advanced Power Settings

- 4. Scroll down to **Battery** and click + to expand the battery options.
- 5. Choose the options below (click **Yes** if a warning appears):

Advanced settings Select the power plan that you want to customize, and then choose settings that reflect how you want your computer to manage power.	Advanced settings Select the power plan that you want to custom and then choose settings that reflect how you v your computer to manage power.
Change settings that are currently unavailable Discharge Battery [Active]	<u>Change settings that are currently unavailable</u> Discharge Battery [Active]
Multimedia settings	Plugged in: 5%
Battery	Low battery notification
Critical battery action	On battery: Off
On battery: Shut down	Plugged in: Off
Plugged in: Do nothing	Low battery action
Low battery level	On battery: Do nothing 🔻
On battery (%); 0 🚍	Plugged in: Do nothing
Plugged in: 0%	Reserve battery level
Critical battery level	On battery: 0%
On hatten: 5%	Plunned in: 0%
* III F	•
<u>R</u> estore plan defaults	<u>R</u> estore plan defaul

- Low battery levels = 0%
 - Critical battery Levels = 1%
 - Low battery action = Do Nothing
 - Critical battery action (On battery) = Shut Down
 - Critical battery action (Plugged in) = Do Nothing

<i>Figure 3 - 9</i>		
Power Options		
Advanced Settings -		
Battery		

How do I fully charge the battery?

When charging the battery, don't stop until the LED charging indicator light changes from orange to green.

How do I maintain the battery?

Completely discharge and charge the battery at least once every 30 days or after about 20 partial discharges.

沃

SLI Multi GPU Configuration & Battery Power Note that due to the high power and system demands created by enabling SLI Configuration, you should not enable SLI configuration if your computer is powered by battery only. If you attempt to run an SLI configuration when the computer is powered by the battery only, then system problems may occur.

If the computer is currently powered by battery only **do not enable SLI configuration**.

If you have currently enabled SLI configuration, and the computer is powered by the AC/ DC adapter, **do not switch to battery power only** (or go to the NVIDIA Control Panel and disable SLI configuration before switching to battery power only).

Power Management

Chapter 4: Drivers & Utilities

This chapter deals with installing the drivers and utilities essential to the operation or improvement of some of the computer's subsystems. The system takes advantage of some newer hardware components for which the latest versions of most available operating systems haven't built in drivers and utilities. Thus, some of the system components won't be auto-configured with an appropriate driver or utility during operating system installation. Instead, you need to manually install some system-required drivers and utilities.

RAID & AHCI Setup

Note that setting up a RAID, or AHCI mode, needs to be done prior to installing the *Windows OS*, and therefore before installing the other drivers listed here (see *"Setting Up SATA RAID or AHCI Mode" on page 7 - 2*).

What to Install

The *Device Drivers & Utilities* + *User's Manual* disc contains the drivers and utilities necessary for the proper operation of the computer.

Table 4 - 1, on page 4 - 3 lists what you need to install and it is very important that the drivers are installed in the order indicated.

Module Driver Installation

The procedures for installing drivers for the PC Camera, WLAN, Fingerprint, Bluetooth and THX TruStudio Audio modules are provided in "*Modules*" on page 7 - 1.

Drivers & Utilities

Driver Installation

Insert the *Device Drivers & Utilities + User's Manual* disc and click *Install Drivers* (button), or *Option Drivers* (button) to access the **Optional** driver menu.



Figure 4 - 1 - Drivers Installer Screen 1

- Check the driver installation order from *Table 4 1*, on page 4 - 3 (the drivers must be installed in this order) which is the same as that listed in the *Drivers Installer* menu below.
- 2. Click to select the driver you wish to install, (you should note down the drivers as you install them).
- 3. Follow the instructions for each individual driver installation procedure as listed on the following pages.



Figure 4 - 2 - Drivers Installer Screen 2

Driver for Windows 7 with Service Pack 1*			
Chipset	Page 4 - 6	Intel Rapid Storage Technology (for RAID & AHCI mode Hard Disk Drives)	Page 7 - 9
Video (VGA)	Page 4 - 6	PC Camera Module	Page 7 - 15
LAN	Page 4 - 7	Wireless LAN Module	Page 7 - 23
Card Reader	Page 4 - 7	Fingerprint Reader Module	Page 7 - 43
TouchPad	Page 4 - 7	Bluetooth Module	Page 7 - 49
Hot Key	Page 4 - 7	THX TruStudio Pro Audio	Page 7 - 64
GameKey Utility	Page 4 - 7	*Note all drivers provided are for Windows 7 with So vice Pack 1.	
USB 3.0	Page 4 - 7		
MEI Driver	Page 4 - 8		
Audio	Page 4 - 8		

Table 4 - 1 - Driver Installation

Note that you need to install both the WLAN & Bluetooth drivers for Intel and 3rd party WLAN & Bluetooth Combo modules.

Drivers & Utilities

Manual Driver Installation

Click the **Browse CD/DVD** button in the *Drivers Installer* application and browse to the executable file in the appropriate driver folder.

Windows Update

After installing all the drivers make sure you enable **Windows Update** in order to get all the latest security updates etc. (all updates will include the latest **hotfixes** from Microsoft). See "*Windows Update*" on page 4 -9 for instructions.

Updating/Reinstalling Individual Drivers

If you wish to update/reinstall individual drivers it may be necessary to uninstall the original driver. To do this go to the **Control Panel** in the *Windows OS* and double-click the **Programs and Features** icon (**Programs > Uninstall a program**). Click to select the driver (if it is not listed see below) and click **Uninstall**, and then follow the on screen prompts (it may be necessary to restart the computer). Reinstall the driver as outlined in this chapter.

If the driver is not listed in the **Programs and Fea**tures menu:

- 1. Click Start, and click Control Panel (or point to Settings and click Control Panel).
- 2. Double-click Device Manager (Hardware and Sound > Device Manager).
- 3. Double-click the **device** you wish to update/reinstall the driver for (you may need to click "+" to expand the selection).
- 4. Click **Driver** (tab) and click the **Update Driver** or **Uninstall** button and follow the on screen prompts.

User Account Control

If a **User Account Control** prompt appears as part of the driver installation procedure, click **Continue/Al-low**, and follow the installation procedure as directed.

Windows Security Message

If you receive a *Windows* security message as part of the driver installation process. Just click "*Install this driver software anyway*" or **Install** to continue the installation procedure.

You will receive this message in cases where the driver has been released after the version of *Windows* you are currently using. All the drivers provided will have already received certification for *Windows*.

New Hardware Found

If you see the message "**New Hardware Found**" during the installation procedure (**other than when outlined in the driver install procedure**), click **Cancel** to close the window, and follow the installation procedure.

Drivers & Utilities

Driver Installation Procedure

Insert the *Device Drivers & Utilities + User's Manual* disc and click *Install Drivers* (button), or *Option Drivers* (button) to access the **Optional** driver menu.

Driver Installation General Guidelines

The driver installation procedure outlined in this Chapter (and in **Chapter 7 Options & Modules**), are accurate at the time of going to press.

Drivers are always subject to upgrade and revision so the exact procedure for certain drivers may differ slightly. As a general guide follow the default on screen instructions for each driver (e.g. **Next > Next > Finish**) unless you are an advanced user. In many cases a restart is required to install the driver.

RAID Note: Setting up a **RAID**, or **AHCI** mode, needs to be done prior to installing the *Windows OS*, and therefore before installing the other drivers listed here.

Chipset

- 1. Click **1.Install Chipset Driver > Yes**.
- 2. Click **Next > Yes > Next > Next**.
- 3. Click **Finish** to restart the computer.

Video (VGA)

- 1. Click **2.Install VGA Driver > Yes**.
- 2. Click **AGREE AND CONTINUE** (button) to accept the terms of the license agreement.
- 3. Click Next.
- 4. Click the **RESTART NOW** button to restart the computer.

After the Video (VGA) driver has been installed, and the system restarted, the OS will automatically run the "Winsat.exe" to rate the performance. Allow time for this process to finish and do not restart during this process (if you have restarted the system see "Windows Update" on page 4 - 9).

LAN

- 1. Click **3.Install LAN Driver > Yes**.
- 2. Click Install.
- 3. Click **Finish** to complete the installation.

Card Reader

- 1. Click **4.Install Cardreader Driver > Yes**.
- 2. Click Install.
- 3. Click **Finish** to complete the installation.

TouchPad

- 1. Click **5.Install Touchpad Driver > Yes**.
- 2. Click Next.
- 3. Click the button to accept the license, and then click **Next**.
- 4. Click **Finish > Restart Now** to restart the computer.

Hot Key

- 1. Click 6.Install Hotkey AP > Yes.
- 2. Click Next > Next.
- 3. Click **Finish > Finish** to restart your computer.

GameKey Utility

- 1. Click **7.Install Gamekey AP > Yes**.
- 2. Click Next.
- 3. Click **Finish** to restart the computer.
- 4. See "Game Keys" on page 2 8 for information.

USB 3.0

- 1. Click **8.Install USB 3.0 Driver > Yes**.
- 2. Click Next.
- 3. Click the button to accept the license and then click **Next**.
- 4. Click **Install > Finish**.

Drivers & Utilities

MEI Driver

- 1. Click **9.Install MEI Driver > Yes**.
- 2. Click Next > Yes > Next > Next.
- 3. Click Finish.

Audio

- 1. Click **10. Install Audio Driver > Yes**.
- 2. Click Next.
- 3. Click **Finish** to restart the computer.

After installing the audio driver the system will not return to the **Drivers Installer** screen. To install any of the optional drivers, eject the *Device Drivers & Utilities* + *User's Manual* disc and then reinsert it (or double-click the disc icon in My Computer), and click **Option Drivers** (button) to access the optional driver menu. It is recommended that you install the **THX Tru Studio Pro Audio** application (see "*THX TruStudio AP Installation*" *on page 7 - 110*) and **Intel Rapid Storage Technology** driver (see "*IRST Driver Installation*" *on page 7 - 8* - required for AHCI & RAID mode hard disks).

(see over)

CP Windows Update

After installing all the drivers make sure you enable **Windows Update** in order to get all the latest security updates etc. (all updates will include the latest **hotfixes** from Microsoft).

To enable Windows Update make sure you are connected to the internet:

- 1. Click Start, and click Control Panel (or point to Settings and click Control Panel).
- 2. Click Check for updates (Security), or doubleclick Security Center and click Windows Update.
- 3. Double-click Check for updates (button).
- 4. The computer will now check for updates (you need to be connected to the internet).
- 5. Click **Install now** (button) to install the updates.

Optional Drivers

See the pages indicated for the driver installation procedures for any modules included in your purchase option.



Figure 4 - 3 - Optional Drivers Installer Screen

Drivers & Utilities

RAID Setup

See "Setting Up SATA RAID or AHCI Mode" on page 7 - 2.

PC Camera

See "PC Camera Module" on page 7 - 15.

Wireless LAN

See "Wireless LAN Module" on page 7 - 23.

Fingerprint Reader Module

See "Fingerprint Reader Module" on page 7 - 43.

Bluetooth Module

See "Bluetooth Module" on page 7 - 49.

THX TruStudio AP

See "THX TruStudio Pro Audio" on page 7 - 64.

Chapter 5: BIOS Utilities

Overview

This chapter gives a brief introduction to the computer's built-in software:

Diagnostics: The POST (Power-On Self Test)

Configuration: The Setup utility

If your computer has never been set up, or you are making important changes to the system (e.g. hard disk setup), then you should review this chapter first and note the original settings found in *Setup*. Even if you are a beginner, keep a record of the settings you find and any changes you make. This information could be useful if your system ever needs servicing.

There is one general rule: *Don't make any changes unless you are sure of what you are doing*. Many of the settings are required by the system, and changing them could cause it to become unstable or worse. If you have any doubts, consult your service representative.

泛

BIOS Screens

Note that the BIOS screens pictured on these pages are intended for guidance in setting up your system's BIOS.

BIOS versions are subject to constant change and revision, therefore your computer's actual screens may appear slightly different from those pictured on these pages.

The Power-On Self Test (POST)

If you enable the **Boot-time Diagnostic Screen** in the Setup Utility, each time you turn on the computer the system takes a few seconds to conduct a **POST**, including a quick test of the on-board RAM (memory).

As the **POST** proceeds, the computer will tell you if there is anything wrong. If there is a problem that prevents the system from booting, it will display a system summary and prompt you to run *Setup*.

If there are no problems, the *Setup* prompt will disappear and the system will load the operating system. Once that starts, you can't get into *Setup* without rebooting.

Failing the POST

Errors can be detected during the **POST**. There are two categories, "fatal" and "non-fatal".

Fatal Errors

These stop the boot process and usually indicate there is something seriously wrong with your system. Take the computer to your service representative or authorized service center as soon as possible.

Non-Fatal Errors

This kind of error still allows you to boot. You will get a message identifying the problem (make a note of this message!) followed by the prompt:

- Press <F1> to resume
- <F2> to enter Setup

Press **F1** to see if the boot process can continue. It may work, without the correct configuration.

Press **F2** to run the **Setup** program and try to correct the problem. If you still get an error message after you change the setting, or if the "cure" seems even worse, call for help.



BIOS Settings Warning

Incorrect settings can cause your system to malfunction. To correct mistakes, return to *Setup* and restore the *Previous Values* with <F2>, or Optimized Defaults with <F3>.

The Setup Utility

The **Aptio Setup Utility** tells the system how to configure itself and manage basic features and subsystems (e.g. port configuration).

Entering Setup


To enter *Setup*, turn on the computer and press **F2** during the **POST**. The prompt "*Press F2 to Enter Setup*" is usually present for a few seconds after you turn on the system. If you get a "Keyboard Error", (usually because you pressed **F2** too quickly) just press **F2** again.

If the computer is already on, reboot using the Ctrl + Alt + Delete combination and then hold down F2 when prompted. The *Setup* main menu will appear.

Setup Screens

The following pages contain additional advice on portions of the *Setup*. Along the top of the screen is a menu bar with menu headings. When you select a heading, a new screen appears. Scroll through the features listed on each screen to make changes to *Setup*.

Instructions on how to navigate each screen are in the box at the bottom right side of the screen.



Setup Menus

The **Setup** menus shown in this section are for **reference** only. Your computer's menus will indicate the configuration appropriate for your model and options.

5

Figure 5 - 1 Navigation Menu

If these tools are confusing, press **F1** to call up a **General Help** screen, and then use the arrow keys to scroll up or down the page.

The **Item Specific Help** on the upper right side of each screen explains the highlighted item and has useful messages about its options.

If you see an arrow \blacktriangleright next to an item, press **Enter** to go to a sub-menu on that subject. The sub-menu screen that appears has a similar layout, but the **Enter** key may execute a command.

Main Menu

Figure 5 - 2 Main Menu

Aptio Setup Ut Main Advanced Security Bo	ility - Copyright (C) 2010 oot Exit	American Megatrends Inc.
System Date System Time SATA Port 0 TOSHIBA MK2565 SATA Port 1 TOSHIBA MK2565 SATA Port 2 MATSHITABD-CMB SATA Port 3 Not Present SATA Port 4 Not Present	(250.0GB)	Set the Date. Use Tab to switch between Data elements.
System Memory: Extended Memory: MB Series: BIOS Revision:	640 KB 4096 MB (DDR3) ********** ******	<pre> →←: Select Screen ↑↓: Select Item </pre>
KBC/EC firmware Revision: VGA Card: VBIOS Revision: VBIOS Build Card:	********* ******** ********* *****	Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save Changes & Exit
Version ******	** Copyright (C) 2010 Amer	ESC: Exit ican Megatrends. Inc.

System Time & Date (Main Menu)

The hour setting uses the 24-hour system (i.e., $\emptyset\emptyset$ = midnight; 13 = 1 pm). If you can change the date and time settings in your operating system, you will also change these settings. Some applications may also alter data files to reflect these changes.

SATA Port 0/1/2/3/4 (Main Menu)

Pressing **Enter** opens the sub-menu to show the configuration of a optical Device/ HDD on the computer's SATA ports.

System/Extended Memory (Main Menu)

This item contains information on the system memory, and is not user configurable. The system will auto detect the amount of memory installed.

BIOS Revision/ KBC/EC firmware Revision / VGA Card etc. (Main Menu) This item contains information on the BIOS version and video card etc., and is not user configurable.

Advanced Menu

Figure 5 - 3 Advanced Menu

ain Advanced Security Bo	OU EXIU	
		Advanced Chipset Control
Advanced Chipset Control		
SATA Mode	[AHCI Mode]	
Legacy USB Support:	[Enabled]	
Boot Logo: Power On Boot Beep:	[Enabled] [Enabled]	
Battery Low Alarm Beep:	[Enabled]	
		→ Select Screen
		↑↓ : Select Item
		Enter: Select
		+/-: Change Opt.
		F1: General Help
		F2: Previous Values
		F3: Optimized Defaults
		F4: Save Changes & Exit
		ESC: Exit

Advanced Chipset Control (Advanced Menu) The sub-menu here allows you to adjust the **Bluetooth Power Setting**.

system. Do not change the mode unless you intend to reinstall your opmake sure you back up all necessary files and data before doing so.

Set the SATA mode BE-FORE installing your

Windows 7 operating

沇 SATA Mode Selection

BIOS Utilities

Bluetooth Power Setting (Advanced Menu > Advanced Chipset Control) You can adjust the Bluetooth module power setting to your preference. The default setting (Disabled) will see the Bluetooth module powered off when the system is started up or restarted. Enabling the power setting will have the module retain the last power status (on or off) before any restart or shut down.

SATA Mode (Advanced Menu)

You can configure SATA (Serial ATA) control to operate in either AHCI (Advanced Host Controller Interface) or RAID (Redundant Array of Independent Disks) modes from this menu. The **SATA mode** should be set **BEFORE installing** an operating system, and after you have backed up all necessary files and data (see sidebar). See "Setting Up SATA RAID Mode" on page 7 - 2 for details if you are configuring you hard disks in a **RAID**.

Legacy USB Support: (Advanced Menu)

Choose "Enabled" if you intend to use USB devices in systems which do not normally support USB functionality (e.g. DOS). The default setting is "Enabled" and does not need to be changed if you intend to use your USB devices in Windows.

Boot Logo: (Advanced Menu)

Use this menu item to enable/disable the Boot Logo screen at system startup.

Power On Boot Beep (Advanced Menu) Use this menu item to enable/disable the beep as the computer starts up.

Battery Low Alarm Beep (Advanced Menu) Use this menu item to enable/disable the battery low alarm beep.

Security Menu

t Supervisor Password	Setup Supervisor Password
	→←: Select. Screen
	↑↓: Select Item
	Enter: Select
	+/-: Change Opt.
	F1: General Help F2: Previous Values
	F3: Optimized Defaults
	F4: Save Changes & Exit
	ESC: Exit



Security Menu

R

The changes you make here affect the access to the **Setup** utility itself, and also access to your machine as it boots up after you turn it on. These settings do not affect your machine or network passwords which will be set in your software OS.

> *Figure 5 - 4* Security Menu

Set Supervisor Password (Security Menu)

You can set a password for access to the **Aptio Setup Utility**. This will not affect access to the computer OS (only the **Aptio Setup Utility**).

Note: To clear existing passwords press **Enter** and type the existing password, then press **Enter** for the new password (without typing any password entry) and **Enter** again to confirm the password clearance.

Boot Menu

Figure 5 - 5 **Boot Menu**

BIOS Screens

Note that the BIOS screens pictured on these pages are intended for guidance in setting up your system's BIOS.

BIOS versions are subject to constant change and revision, therefore your computer's actual screens may appear slightly different from those pictured on these pages.

Boot Sequence:		Keys used to view or configur devices:
L: SATA ODD 2: USB ODD	P2: MATSHITABD-CMB UJ141AL	Up and Down arrows select a device.
3: SATA HDD 4: SATA HDD 5: SATA HDD 6: USB KEY	Intel MyRAID	<f5> and <f6> moves the devic up or down.</f6></f5>
7: USB KEY 8: USB HDD		
9: USB HDD 10:PCI BEV	JMC25X Gigabit Ethernet Controller	
		→ Select Screen
		↑↓ :Select Item
		Enter: Select
		+/-: Change Opt.
		F1: General Help F2: Previous Values
		F2: Previous Values F3: Optimized Defaults
		F4: Save Changes & Exit
		ESC: Exit

When you turn the computer on it will look for an operating system (e.g. *Windows* 7) from the devices listed in this menu, and **in this priority order**. If it cannot find the operating system on that device, it will try to load it from the next device in the order specified in the **Boot priority order**. Item specific help on the right is available to help you move devices up and down the order.

Boot Sequence (Boot Menu)

Use the arrow keys to move up and down the menu and use the **F5** and **F6 keys** to move the device's boot priority up and down the list (the selected device will be highlighted in white).

Exit Menu

Figure 5 - 6 Exit Menu

Aptio Setup Utility - Copyright (C) 2010 American Megatrends Inc. Main Advanced Security Boot Exit		
Save Changes and Reset Exit Discarding Changes Load Setup Defaults Discard Changes Save Changed	Reset the system after saving the changes.	
	<pre>→←:Select Screen ↑↓:Select Item Enter: Select +/-: Change Opt. F1: General Help F2: Previous Values F3: Optimized Defaults F4: Save Changes & Exit ESC: Exit</pre>	
Version ******* Copyright (C)	2010 American Megatrends. Inc.	

Choosing to *Discard Changes*, or *Exit Discarding Changes*, will wipe out any changes you have made to the *Setup*. You can also choose to restore the original *Set-up* defaults that will return the *Setup* to its original state, and erase any previous changes you have made in a previous session.

Chapter 6: Upgrading The Computer

Overview

This chapter contains information on upgrading the computer. Follow the steps outlined to make the desired upgrades. If you have any trouble or problems you can contact your service representative for further help. Before you begin you will need:

- A small crosshead or Phillips screwdriver
- A small regular slotted (flathead) screwdriver
- An antistatic wrist strap

Before working with the internal components you will need to wear an antistatic wrist strap to ground yourself because static electricity may damage the components.

The chapter includes:

- Removing the Battery
- Upgrading the Optical (CD/DVD) Device
- Upgrading the Hard Disk Drive(s)
- Upgrading the System Memory (RAM)
- Upgrading the Video Card

Please make sure that you review each procedure before you perform it.

Warranty Warning

Please check with your service representative before undertaking any upgrade procedures to find out if this will VOID your warranty.

6



Power Safety Warning

Before you undertake any upgrade procedures, make sure that you have turned off the power, and disconnected all peripherals and cables (including telephone lines). It is advisable to also remove your battery in order to prevent accidentally turning the machine on.

When Not to Upgrade

These procedures involve opening the system's case, adding and sometimes replacing parts.You should **not** perform any of these upgrades if:

- Your system is still under warranty or a service contract
- You don't have all the necessary equipment
- You're not in the correct environment
- You doubt your abilities

Under any of these conditions, contact your service representative to purchase or replace the component(s).

Removal Warning

沇

When removing any cover(s) and screw(s) for the purposes of device upgrade, remember to replace the cover(s) and screw(s) before turning the computer on.


Upgrading the Processor

If you want to upgrade your computer by replacing the existing processor with a faster/new one you will need to contact your customer service representative. We recommend that you do not do this yourself, since if it is done incorrectly you may damage the processor or mainboard.

Removing the Battery

If you are confident in undertaking upgrade procedures yourself, for safety reasons it is best to remove the battery.

- 1. Turn the computer off and turn it over.
- 2. Slide the latch (1) in the direction of the arrow.
- 3. Slide the latch 2 in the direction of the arrow, and hold it in place.
- 4. Lift the battery 3 up and out of the battery bay.
- 5. To reinsert the battery simply reverse this process.



泛

Warranty Warning

Please check with your service representative before undertaking any upgrade procedures to find out if this will VOID your warranty.

Figure 6 - 1 Battery Removal

Upgrading the Optical (CD/DVD) Device

- 1. Turn off the computer, and turn it over and remove the battery.
- 2. Locate the hard disk bay cover and remove screws (1 (3).
- 3. Remove the hard disk bay and cover 4.
- 4. Remove the screw **5** from the optical device drive.
- 5. Push the optical device drive out of the bay and reverse the process to install a new ODD.



Figure 6 - 2 Removing the CD/ DVD Device

Upgrading the Hard Disk Drive(s)

The hard disk drive(s) can be taken out to accommodate other 2.5" serial (SATA) hard disk drives with a height of 9.5mm (h) (see "*Storage*" on page C - 2). Follow your operating system's installation instructions, and install all necessary drivers and utilities (as outlined in "*Drivers & Utilities*" on page 4 - 1), when setting up a new hard disk.

Removing the Hard Disk(s) in the Primary HDD Bay

- 1. Turn off the computer, and turn it over and remove the battery.
- 2. Locate the hard disk bay cover and remove screws 1 3.
- 3. Remove the hard disk bay and cover 4.





汃

HDD System Warning

New HDD's are blank. Before you begin make sure: You have backed up any data you want to keep from your old HDD.

You have all the CD-ROMs and FDDs required to install your operating system and programs.

If you have access to the internet, download the latest application and hardware driver updates for the operating system you plan to install. Copy these to a removable medium.

Figure 6 - 3 Component Bay Cover Screws

- 4. Remove screws **5 8** from the hard disk assembly.
- 5. Disconnect the hard disk cable 9.
- 6. Remove the hard disk assembly by pulling the tab to lift the assembly out of the bay **10**.






Figure 6 - 4 Bay Cover Removal & Hard Disk Assembly Screws

- 7. Remove screws (1) (18) (depending on how many hard disks you have installed in the assembly).
- 8. Separate the hard disk board (19) from the case (20).
- 9. Separate the hard disk(s) 21 & 22 from the case.
- 10. Reverse the process to install any new hard disk(s).





Upgrading the Hard Disk Drive(s) 6 - 7

Removing the Hard Disk in the Secondary HDD Bay

- 1. Turn off the computer, and turn it over and remove the battery.
- 2. Remove the optical device drive "Upgrading the Optical (CD/DVD) Device" on page 6 4.
- 3. The secondary hard disk bay is located under the optical device drive.
- 4. Remove screws 23 28
- 5. Remove the retaining pin (29) and disconnect the hard disk cable (30).
- 6. Lift the hard disk assembly **31** out of the compartment.






Figure 6 - 6 Secondary HDD Assembly Removal



- 7. Remove the screws 32 35 to release the hard disk from the case 36.
- 8. Remove the cable 37.
- 9. Reverse the process to install any new hard disk(s).



HDD Installation Make sure that when you are reinserting the retaining pin that it is orientated as per the picture below (see also Figure 6 - 6 on page 6 - 8).



Figure 6 - 7 Secondary HDD Case & Cable Removal

Upgrading the System Memory (RAM)

The computer has **three** memory sockets for 204 pin Small Outline Dual In-line (SO-DIMM) **DDR III (DDR3)** type memory modules (see "*Memory*" on page C - 2). The total memory size is automatically detected by the POST routine once you turn on your computer.

Removing the Primary System Memory (2 memory sockets)

- 1. Turn off the computer, and turn it over and remove the battery.
- 2. Locate the component bay cover and remove screws 1 4



Figure 6 - 8 Component Bay Cover Screws

- 3. Carefully (three fans and cables are attached to the under side of the cover) lift up the bay cover.
- 4. Carefully disconnect the fan cables **5** in the order **A**, **B** & **C** and remove the cover **6**.
- 5. The primary memory sockets are visible at point **7**.






Figure 6 - 9 Component Bay Cover Removal


- 6. Gently pull the two release latches (8 & 9) on the sides of the memory socket in the direction indicated below.
- 7. The RAM module **10** will pop-up, and you can remove it.

Be careful not to touch the metal pins on the module's connecting edge. Even the cleanest hands have oils which can attract particles, and degrade the module's performance.

沁

Contact Warning

Figure 6 - 10 **RAM Module Removal**



- 8. Pull the latches to release the second module if necessary.
- 9. Insert a new module holding it at about a 30° angle and fit the connectors firmly into the memory socket.
- 10. The module's pin alignment will allow it to only fit one way. Make sure the module is seated as far into the socket as it will go. DO NOT FORCE the module; it should fit without much pressure.
- 11. Press the module in and down towards the mainboard until the socket levers click into place to secure the module.

6 - 12 Upgrading the System Memory (RAM)

6

- 12. Reconnect the fan cables **5** in the order **C**, **B** & **A**.
- 13. Reinsert the component bay cover 6, and secure with the screws 1 4.








Figure 6 - 11 Component Bay Cover Screws & Cover Insertion

- 14. Restart the computer to allow the BIOS to register the new memory configuration as it starts up.
- 15. Restart the computer to allow the BIOS to register the new memory configuration as it starts up.

Removing the Secondary System Memory (1 memory socket)

- 1. Turn off the computer, and turn it over and remove the battery.
- 2. Remove screws (1) & (2) from the bottom of the computer.



 Turn the computer over, open the Lid/LCD, and carefully (a cable is connected to the underside of the LED cover module) unsnap up the LED cover module from point 3 on the right.





Figure 6 - 13 LED Cover Module Removal

6 - 14 Upgrading the System Memory (RAM)

4. Lift up the LED cover module 4 and disconnect cable 5.

5. Remove screws 6 - 10 from the keyboard.

- *Figure 6 15* Disconnect the Keyboard Locking Collar
- 6. Carefully lift the keyboard up, being careful not to bend the keyboard ribbon cable.
- 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0
 0

111



6

Figure 6 - 16 **Keyboard Removal**


- 8. Remove the keyboard **13**, and then remove screws **14 16** from the keyboard shielding plate.

Figure 6 - 17 Keyboard Shielding Plate Screws

7. Disconnect the keyboard ribbon cable **11** from the locking collar socket **12**.



9. Remove the keyboard shielding plate (17).



10. Gently pull the two release latches (18 & 19) on the sides of the memory socket in the direction indicated below.




Figure 6 - 18 Keyboard Shielding Plate Removal

Contact Warning

Be careful not to touch the metal pins on the module's connecting edge. Even the cleanest hands have oils which can attract particles, and degrade the module's performance.


Figure 6 - 19 RAM Module Release Latches

11. The RAM module 20 will pop-up, and you can remove it.

Figure 6 - 20 **RAM Module Removal**

Contact Warning

Be careful not to touch the metal pins on the module's connecting edge. Even the cleanest hands have oils which can attract particles, and degrade the module's performance.




- 12. Insert a new module holding it at about a 30° angle and fit the connectors firmly into the memory socket.
- 13. The module's pin alignment will allow it to only fit one way. Make sure the module is seated as far into the socket as it will go. DO NOT FORCE the module; it should fit without much pressure.
- 14. Press the module in and down towards the mainboard until the socket levers click into place to secure the module.
- 15. Replace the screws, shielding plate and keyboard (make sure you reconnect the keyboard cable).

6 - 18 Upgrading the System Memory (RAM)

6


- 16. Snap the LED cover module down at the top of the module at points 21 & 22.
- 17. Push the LED cover module down on the left side at point 23, and then slide the module to the right (as illustrated) and snap down to secure it in place.







- 18. Replace the screws on the bottom of the computer (see *Figure 6 12*).
- 19. Restart the computer to allow the BIOS to register the new memory configuration as it starts up.






Warranty Warning

Please check with your service representative before undertaking any upgrade procedures to find out if this will VOID your warranty.

Figure 6 - 22 Component Bay Cover Screws & Cover Removal




Upgrading the Video Card


If you intend to upgrade or add another VGA card follow the procedures outlined here. However please check with your service representative first to make sure your computer can support more than one video card, and that you are not going to void your warranty. Pay careful attention to the alignment of any video card into the slot on the mainboard.


- 1. Turn off the computer, and turn it over and remove the battery.
- Locate the component bay cover and remove screws 1 4.
- 3. Carefully (three fans and cables are attached to the under side of the cover) lift up the bay cover.
- 4.Carefully disconnect the fan cables **5** in the order **A**, **B** & **C** and remove the cover **6**.





- 5. Remove screws **7 10** in the order indicated on the label (and on the heat sink unit itself).
- 6. Remove the heat sink unit (1) (two heat sink units are pictured here).





Caution

The heat sink, and video card area in general, contains parts which are subject to high temperatures. Allow the area time to cool before removing these parts.

Figure 6 - 23 Heat Sink Screws & Heat Sink Removal

Upgrading the Video Card 6 - 21


Caution

The heat sink, and video card area in general, contains parts which are subject to high temperatures. Allow the area time to cool before removing these parts.

Figure 6 - 24 Video Card Removal


- 7. Remove screws 12 & 13 from the video card (two video cards are pictured).
- 8. Carefully remove the video card 14.
- If your system includes two video cards you will need to disconnect the cable 15 between the master and slave cards (do not forget to reconnect the cable if you are replacing two cards).





Installing a New Video Card

1. Prepare to fit the video card into the slot by holding it at about a 30° angle.



2. The card needs to be fully into the slot, and the video card and socket have a guide-key and pin which align to allow the card to fit securely.

泛


Contact Warning

Be careful not to touch the metal pins on the VGA card's connecting edge. Even the cleanest hands have oils which can attract particles, and degrade the module's performance.

6

Figure 6 - 25 Video Card Insertion

- 3. Fit the connectors firmly into the socket, straight and evenly.
- 4. DO NOT attempt to push one end of the card in ahead of the other.







- 5. The card's pin alignment will allow it to only fit one way. **Make sure the module is seated as far into the socket as it will go** (none of the gold colored contact should be showing). DO NOT FORCE the card; it should fit without much pressure.
- 6. Press the card down onto the board using two hands at points **16** & **17** as indicated above.

Figure 6 - 26 Video Card Insertion Procedure

- 7. Secure the card with screws (2 & (3) (*Figure 6 24 on page 6 22*).
- 8. Place the heatsink back on the card, and secure the screws in the order indicated in *Figure 6 23 on page 6 21*.
- 9. Reconnect the fan cables **5** in the order **C**, **B** & **A**.
- 10. Reinsert the component bay cover 6, and secure with the screws 1 4.








Figure 6 - 27 Component Bay Cover Screws & Cover Insertion

Chapter 7: Modules

Overview

This chapter contains information on the various modules (some of which are **op-tional**) which may come with your computer, depending on the configuration purchased. If you are unsure please contact your service representative.

The chapter includes information on the following:

- Setting Up SATA RAID or AHCI Mode
- PC Camera Module
- Wireless LAN Module
- Fingerprint Reader Module
- Bluetooth Module
- THX TruStudio Pro Audio

Ň

RAID Hard Disks

All hard disks in a RAID should be identical (the same size and brand) in order to prevent unexpected system behavior.

SATA Mode Selection

The SATA mode selection should be made **be**fore installing your operating system.

DO NOT change your selected SATA mode unless you intend to reinstall your operating system. Make sure you have backed up all your data before doing so.

Setting Up SATA RAID or AHCI Mode AHCI Mode

Advanced Host Controller Interface (AHCI) is an interface specification that allows the storage driver to enable advanced serial ATA features such as Native Command Queuing (for maximum hard disk efficiency and performance). AHCI mode can be supported by one or two hard disks. Make sure you install the **Intel® Rapid Storage Technology** application if you have set up your hard disk(s) in **AHCI** mode (see *"Intel Rapid Storage Technology" on page 7 - 9*)

RAID

To configure your RAID (Redundant Array of Independent Disks) system in Striping (RAID 0), Mirroring (RAID 1) or Recovery modes (see *Table 7 - 1, on page 7 - 3*) you will require **at least two identical** (see sidebar) hard disks; to configure your system in Parity Across Disks (RAID 5) mode you will require **three hard disks** installed. Note that if you are using **Advanced format hard disks that have a 4KB physical sector size**, and you are **installing** a *Windows 7* release pre **Service Pack** 1, you will need to install a driver from the *Device Drivers & Utilities + User's Manual disc* at OS installation (see page 8 - 18).

Intel® Rapid Storage Technology Application

Make sure you install the Intel[®] Rapid Storage Technology application if you have set up your hard disk(s) in RAID mode (see *"Intel Rapid Storage Technology" on page 7 - 9*).

RAID Level	Description
RAID 0	Two Identical drives reading and writing data in parallel to increase performance . RAID 0 implements a striped disk array and the data is broken into blocks and each block is written to a separate disk drive.
RAID 1	Two Identical drives in a mirrored configuration used to protect data . Should a drive that is part of a mirrored array fail, the mirrored drive (which contains identical data) will handle all the data. When a new replacement drive is installed, data to the new drive is rebuilt from the mirrored drive to restore fault tolerance.
RAID 5	Identical drives (at least three drives must be used) in a parity across disks configuration are used to protect data and increase performance . A RAID 5 array can withstand a single disk failure without losing access to data.
Recovery	Two Identical drives copying data between a master and a recovery disk. This provides more control over how data is copied between the master and recovery drives, fast volume updates and the ability to view the data in <i>Windows Explorer</i> .

Table 7 - 1RAID Levels



Array Types

A **Mirrored Array** (**RAID 1**) provides full data protection, as data can simply be copied from a healthy disk to a replacement for any failed disk.

A **Striped Array** (**RAID 0**) is **NOT** faulttolerant. The failure of one drive will result in the loss of all data in the array. It is designed to increase disk performance by spreading the I/O load across the channels and drives.

Prepare the following before setting up your serial ATA hard disks in **RAID** mode (to configure **AHCI** mode you do not need to prepare any extra hard disks but will need to install the **Intel® Rapid Storage Technology** application):

- 1. The Microsoft Windows 7 OS DVD.
- 2. A hard disk installed in the Primary HDD bay. AND

For RAID levels 0/1 and Recovery: A second (identical) hard disk installed in the Primary HDD bay.

For RAID level 5: A third (identical) hard disk installed in the Secondary HDD bay.

3. The Device Drivers & Utilities + User's Manual disc.

Note that if you are using Advanced format hard disks that have a 4KB physical sector size, and you are installing a *Windows 7* release pre Service Pack 1, you will need to install a driver from the *Device Drivers & Utilities + User's Manual disc* at OS installation (see page 8 - 18).

SATA RAID Setup Procedure (BIOS)

- 1. Start-up your notebook computer and press <F2> to enter the BIOS.
- 2. Go to the Advanced menu, select "SATA Mode" and press Enter (see page 5 8).
- Select "RAID Mode".
- 3. Go to the **Boot** menu.
- Set the DVD-ROM Drive (make sure the Microsoft Windows 7 OS DVD is inserted) as the first device in the boot order from the Boot menu (see "Boot Menu" on page 5 - 15).
- 5. Select **Save Changes and Reset** from the **Exit** menu (or press **F4** and Enter) and press **Enter** to exit the BIOS and reboot the computer.
- 6. See the instructions in "RAID Setup (Intel Matrix)" on page 7 6.

RAID Setup (Intel Matrix)

1. As the computer starts up press **Ctrl + i** to enter RAID configuration menu.

Figure 7 - 1 Intel(R) Rapid Storage Technology Option ROM

Recovery Level

When selecting disks for the Recovery RAID level you will need to use the **Tab** key to select a **Mas**ter disk, and the **Space** key to select a **Recov**ery disk.

You can select the synchronization between the disks to be **Continuous** (automatic) or **On Request** (manually).

	MAIN	MENU			
2. Delete	RAID Volume RAID Volume Disks to Non-RAID				
RAID Volumes: None Defined					
Physical Devices: Port Drive Model	Serial #		Type/Status(Vol ID)		
	55GS X07STINOT		Non-SAID Disk		
[1] -Select	[ESC]-Exit	[2]	MTER]-Select		

- 2. Select 1.Create RAID Volume and press Enter.
- 3. Type the **RAID volume name** and then press Tab or Enter to advance to the next field.
- Specify (use the up and down arrow keys) the RAID level (RAID 0, RAID 1 or Recovery - see Table 7 - 1, on page 7 - 3) and then press Tab or Enter to advance to the next field.

7 - 6 Setting Up SATA RAID or AHCI Mode

7

- 5. Press Enter and the system will select the physical disks to use (see sidebar for **Recovery** Level).
- 6. Press Enter and select (if applicable) the Strip Size (best set to default).
- 7. Press Enter and select the Capacity size (best set to default).
- 8. Press Enter to select Create Volume.
- 9. Press Enter to create the volume, and confirm the selection by pressing Y.
- 10. This will now return to the main menu.

			N MENU			
	1. Create RAID Volume 4. Recovery Volume Opt			Options		
		e RAID Volume	5.			
		Disks to Non-RAID	6,			
		DISK/VOLON		ATION 1 =		
RAID	Volumes:					
ID	Name	Level	Strip	Size	Status	Bootable
0	MYRAID	Recovery(Cont.)	N/A	232.9GB		Yes
Phys	ical Devices:					
Port Drive Model		Serial #	# Size Type/Sta		tus (Vol ID)	
1		65GS X07ST1MYT			Master Disk(0)	
2	TOSHIBA MK25	65GS X07STINOT		232.8GB	Recovery Disk(0)	

11. Select **5.Exit** and press Enter, then press **Y** to exit the RAID configuration menu.

Recovery Level

ß

When selecting disks for the Recovery RAID level you will need to use the **Tab** key to select a **Master** disk, and the **Space** key to select a **Recovery** disk.

You can select the synchronization between the disks to be **Continuous** (automatic) or **On Request** (manually).

> *Figure 7 - 2* **RAID Created**

Setting Up SATA RAID or AHCI Mode 7 - 7

Win7 (pre SP1) & Advanced Format Disks in a RAID

ß

Note that if you are installing a Windows 7 OS pre Service Pack 1, and you are using Advanced format hard disks that have a 4KB physical sector size, you will need to install a driver from the Device Drivers & Utilities + User's Manual disc at OS installation (see page 8 - 18).

- 12. Make sure the *Windows* **7** OS DVD is in the DVD drive. and as the computer starts up it will automatically boot from the *Windows* **7** OS DVD (you will be prompted to press a key to boot from the DVD).
- Press Enter to continue installing the operating system as normal (see your Windows documentation if you need help on installing the Windows OS - see sidebar).
- Install the Windows drivers from the Device Drivers & Utilities + User's Manual disc as per Table 4 1, on page 4 3 (make sure you install the Intel Rapid Storage Technology driver see "IRST Driver Installation" on page 7 9).

Intel Rapid Storage Technology

The Intel Rapid Storage Technology application provides high-performance SATA and SATA RAID capabilities. Install the Intel Rapid Storage Technology application to support your RAID system or SATA drive if set up in AHCI mode in the BIOS (see "SATA Mode (Advanced Menu)" on page 5 - 9). Make sure you have installed all the drivers from the Device Drivers & Utilities + User's Manual disc as per Table 4 - 1, on page 4 - 3 before installing the IRST driver.

IRST Driver Installation

- 1. Insert the *Device Drivers & Utilities* + *User's Manual* disc into the CD/ DVD drive.
- 2. Click **Option Drivers** (button).
- 3. Click 6.Install IRST Driver > Yes.
- 4. Click (click the tickbox if you want to install the *Intel*® *Control Center* see sidebar) Next > Next > Next > Next > Next.
- 5. Click **Finish** to restart the computer (you will need to restart the system again after the computer has rebooted).

See the following pages for more information if you have set your hard disks up in a RAID configuration.

Intel® Control Center

R

The **Intel® Control Center** provides a central starting point to make it easier to find any Intel® programs you need to use.

Click the tickbox in the first installation screen of the setup program to install the control center.

Intel® Rapid Storage Technology for RAID Systems

Intel® Rapid Storage Technology application displays status information on your RAID configuration. Run the **Intel® Rapid Storage Technology** application from the **Intel** item in the **All Programs** menu.

When the **Intel® Rapid Storage Technology** application is launched the system will open the **Status** window. Here you can view the general health of the storage system. Various volume creation and management options are available depending on the system's status.





Figure 7 - 3 Intel® Rapid Storage Technology Status

Intel® Rapid Storage Technology Help

If a hard drive member of a RAID volume is reported as "**Degraded**" or "**Failed**" it may be possible to recover the volume. If the volume cannot be restored then you will need to recreate the RAID volume and restore the data from a back up. Click the **Help** menu (or press **F1**) for instructions on how to recover or recreate RAID Volumes.



Help

B

Click the **Help** (or press **F1**) menu button at the top of the **Intel® Rapid Storage Technology** application.

Click **Contents** to view the general list of subjects covered, click **Index** or **Search** for a more specific help topics on a particular item.

Click <u>More help on</u> <u>this page</u> at the bottom of any page for page specific help.

> Figure 7 - 4 Intel® Rapid Storage Technology Help

RAID Volume Data Verification and Repair

The RAID volume data verification process identifies any inconsistencies or bad data on a RAID 0, RAID 1 or RAID 5 volume. The table outlines what occurs for each RAID level:

RAID Level	Verify	Verify & Repair
RAID 0	Bad blocks are identified.	N/A
RAID 5	Bad blocks are identified. Parity is recalculated and compared to the stored parity for that stripe.	Bad blocks are reassigned. If the newly calculated parity does not match the stored parity, the stored parity is overwritten with the newly calculated parity.
RAID 1	Bad blocks are identified. Data on the mirrored drive is compared to data on the source drive.	Bad blocks are reassigned. If the data on the mirrored drive does not match the data on the source drive, the data on the mirrored drive is overwritten by the data on the source.

Replacing and Reverting Recovery and Master Volumes

If a master or recovery drive fails you will need to add a new identical drive and rebuild the recovery volume to the drive. You can also revert the master drive to the state of the previous volume update. For details on how to do this see the help file *"Intel® Rapid Storage Technology Help" on page 7 - 11*.See over for details on how to verify and repair RAID volume data. Verification will identify and repair data inconsistencies on the volume.

Table 7 - 2RAID LevelVerification &Repair Status

Verifying and Repairing RAID Volume Data

- 1. Before verifying the volume data you will need to initialize the volume.
- 2. Run the Intel® Rapid Storage Technology application from the Intel item in the All Programs menu.
- 3. Click Manage and click Advanced.
- 4. Click Initialize and click Yes (button) to begin the process.
- 5. The completion percentage will be listed under Status.




Figure 7 - 5 Intel® Rapid Storage Technology Initialize

- 6. Click Advanced and click Verify, then click Verify (button) to begin the process.
- 7. The completion percentage will be listed under **Status** (verifying and repairing).




Figure 7 - 6 Intel® Rapid Storage Technology Verify

7 - 14 Intel Rapid Storage Technology

PC Camera Module

Before installing the driver, make sure the PC Camera is on. Use the Fn + F10 key combination or Touch Sensor Instant Key $\textcircled{\begin{tmatrix} \hline \mbox{0} \end{bmatrix}}$ to toggle power to the PC Camera module. When the PC Camera module is powered on the $\fbox{\begin{tmatrix} \hline \mbox{0} \end{bmatrix}}$ LED will be highlighted and the indicator $\fbox{\begin{tmatrix} \hline \mbox{0} \end{bmatrix}}$ will briefly be displayed. Make sure you install the drivers in the order indicated in *Table 4 - 1, on page 4 - 3*.

There are a number of different camera modules available with this computer model series. You will have the appropriate application installed for your camera (note that some versions of the camera application do not support the zoom function). **Make sure you access the application via the desktop shortcut**.

汃

PC Camera Application and Power-Saving States

If the computer enters **Sleep** or **Hibernate** mode while running the camera application, the program will stop running, and will need to be restarted when the system resumes from the power-saving state.

泛

Latest PC Camera Driver Information

Check the **Device Drivers** & **Utilities + User's Manual disc** and any accompanying insert pages, for the latest updated information on the PC Camera driver, which may override the information provided here.

PC Camera Display

The PC Camera application software needs to be run while the *default notebook LCD* is the selected display device.

After a camera picture is obtained on the default notebook LCD, you may then use the Fn + F7 to toggle through the display modes (give the screen time to refresh).

PC Camera Driver Installation


- 1. Insert the *Device Drivers & Utilities* + *User's Manual* disc into the CD/ DVD drive.
- 2. Click **Option Drivers** (button).
- 3. Click **1.Install Webcam Driver > Yes**.
- 4. Click **Next** > **Finish** to restart the computer. Run the camera application program from the desktop shortcut (if the hardware is turned off use the **Fn** + **F10** key combination to turn it on again).

PC Camera Audio Setup

If you wish to capture video & **audio** with your camera, it is necessary to setup the audio recording options in *Windows*.

- 1. Click Start, and click Control Panel (or point to Settings and click Control Panel).
- 2. Click Sound @ (Hardware and Sound).
- 3. Click **Recording** (tab).
- 4. Right-click **Microphone** (Realtek High Definition Audio) and make sure the item is not disabled.
- 5. Double-click Microphone (or select Properties from the right-click menu).
- 6. Click Levels (tab), and adjust the Microphone and Microphone Boost sliders to the level required.
- 7. Click **OK** and close the control panels.
- 8. Run the camera application program from the desktop shortcut.
- 9. Go to the **Devices** menu heading and select **Microphone** (**Realtek...**) (it should have a tick alongside it).
- 10. Go to the **Capture** menu heading and select **Capture Audio** (it should have a tick alongside it).
- To obtain the best sound recording quality enable Noise Suppression in the Realtek HD Audio Manager control panel (see "Setup for Audio Recording" on page 2 - 10).

Figure 7 - 7 Audio Setup for PC Camera



Camera Application

The camera application is a video viewer for general purpose video viewing and testing, and for capturing video files to .avi format.

- 1. Run the camera application from the desktop shortcut (it is recommended that you **set the capture file** before the capture process **see below**).
- 2. Go to the **Capture** menu heading (if you wish to capture audio check "*PC Camera Audio Setup*" on page 7 17) and select **Start Capture**.
- 3. Click **OK/Yes** (the file location will be displayed in the pop-up box) to start capturing the video, and press **Esc** to stop the capture (you can view the file using the **Windows Media Player**).

Set Capture File

Prior to capturing video files you may select the **Set Capture File..** option in the **File** menu, and set the file name and location before capture (this will help avoid accidentally overwriting files). Set the name and location then click **Open**, then set the **"Capture file size:"** and click **OK**. You can then start the capture process as on the previous page.

Note the important information in *"Reducing Video File Size" on page 7 - 20* in order to save file space, and help prevent system problems.

Reducing Video File Size

Note that capturing high resolution video files requires a substantial amount of disk space for each file. After recording video, check the video file size (right-click the file and select **Properties**) and the remaining free space on your hard disk (go to **My Computer**, right-click the hard disk, and select **Properties**). If necessary you can remove the recorded video file to a removable medium e.g. CD, DVD or USB Flash drive.

Note that the *Windows* system requires a minimum of **15GB** of free space on the **C**: **drive** system partition. In order to prevent system problems it is recommended that you save the captured video file to a location other than the **C**: **drive** (see "*Set Cap-ture File*" *on page* 7 - *19*), limit the file size of the captured video or reduce video resolution (see below).

To Reduce Video Resolution Output Size:

- 1. Run the camera application program from the desktop shortcut.
- 2. Go to Options and scroll down to select Video Capture Pin....
- 3. Click the **Output Size** drop box and select a lower resolution size in order to reduce the captured file size.
- 4. Click OK.

Eliminating Screen Flicker

If you find that the video screen in the camera program is flickering, you can try to adjust the setting in the **Video Capture Filter** options.

- 1. Run the camera application from the desktop shortcut.
- 2. Go to Options and scroll down to select Video Capture Filter....
- 3. Click either 50Hz or 60Hz under Frequency (Anti Flicker).

deo Proc Amp Camera C	an initial	Auto
Brightness	·	40
Contrast	·0	40
Hue		0
Saturation	·	50
Sharpness		6
Gamma		5
White Balance	0	
Backlight Comp	0	0
Color <u>E</u> nabl	e <u>P</u> owerLine Frequency (Anti Flicke) <u>D</u> efault	50 Hz 50 Hz 60 Hz



Latest PC Camera Driver Information

Check the **Device Driv**ers & Utilities + User's **Manual disc**, and any accompanying insert pages, for the latest updated information on the PC Camera driver, which may override the information provided here, including the figures pictured here.

Figure 7 - 8 Video Capture Filter



Snapshot Folder

The Snapshot folder's default location is on the desktop. Do not move this folder or an error may appear when you try to take a still picture.

If you accidentally delete or move the folder, you can create a new Snapshot folder on the desktop in order to capture the files.

Taking Still Pictures

The camera application allows you to take still pictures.

- 1. Run the camera application from the desktop shortcut.
- 2. Go to **Options** and select **Take Picture**.
- 3. The picture (in JPEG format) will be placed in the **Snapshot** folder desktop.



Wireless LAN Module

If you have included an **Intel**® or **3rd Party 802.11b/g/n WLAN module** in your purchase option, make sure that the Wireless LAN module is on before installing the driver.

Use the Fn + F11 key combination or Touch Sensor Instant Key $\boxed{}$ to toggle power to the Wireless LAN module. When the WLAN module is powered on, the $\boxed{}$ LED will be highlighted and the indicator $\boxed{}$ will briefly be displayed. Make sure you install the drivers in the order indicated in *Table 4 - 1, on page 4 - 3*. The operating system is the default setting for Wireless LAN control in *Windows 7*.

Note that you need to install both the WLAN & Bluetooth drivers for Intel and 3rd party WLAN & Bluetooth Combo modules.

汃

Wireless Device Operation Aboard Aircraft

The use of any portable electronic transmission devices aboard aircraft is usually prohibited. Make sure the module(s) are OFF if you are using the computer aboard aircraft.

Use the **Fn + F11** key combination/Touch Sensor Key to toggle power to the WLAN module, and check the LED to see if the module is powered on or not (see Table 1 - 3, on page 1 - 11/ Table 1 - 2, on page 1 - 9).



Access the Intel PRO-Set Wireless tools (Statistics and Diagnostic tools) from the Start menu (Start > Programs/All Programs > Intel PROSet Wireless). These tools provide diagnostic and information statistical only (use the WLAN control in Windows to connect to a WLAN access point).

Intel® Wi-Fi Link Series Driver Installation

If you see the message "Found New Hardware" click Cancel to close the window.

- 1. Make sure the module is powered on, then insert the *Device Drivers & Utilities* + *User's Manual* disc into the CD/DVD drive.
- 2. Click **Option Drivers** (button).
- 3. Click 2.Install WLAN Driver > Yes.
- 4. Click Next > Next.
- 5. Click the button to accept the license and click Next.
- 6. Click **Next > Next > Finish**.

Note: The operating system is the default setting for Wireless LAN control in *Win-dows* (see overleaf).

802.11b/g/n Driver Installation

- 1. Make sure the module is powered on, then insert the *Device Drivers & Utilities* + *User's Manual* disc into the CD/DVD drive.
- 2. Click **Option Drivers** (button).
- 3. Click 2.Install WLAN Driver > Yes.
- 4. Choose the language you prefer and click **Next > Next**.
- 5. Click **Finish** to restart the computer.

Note: The operating system is the default setting for Wireless LAN control in *Win-dows* 7 (see overleaf).

Connecting to a Wireless Network in Windows 7

Make sure the Wireless LAN module is turned on.

1. **Click** the taskbar wireless icon , and then double-click an access point to connect to or click to **Open Network and Sharing Center** if you do not see a network you want to connect to in the taskbar menu (a list of options will appear allowing setting changes, and creating a new network).

Not connected	49	Control Panel +	Network and Internet Network and Sharing Center	🔹 👍 🛛 Saranch Control Ravel	ļ
Connections are available		Control Panel Home Manage wreless networks Change adapter settings Change advanced sharing	View your basic network information and set up of	connections See full map	
Wireless Network Connection ZyXEL PDA_DLINK CA00	102 100- 102	Lange shaked sampy	(This computer) View your active networks Change your networking settings Set up a new connection or network Set up a wireless, broadband, dial-up, and hor, or VPH- Connect to a memory Connect	connection: or set up a router or access point.	
ADSL-LINKSYSY-N DI-524K DWL-g	lite- lite- lite-	See ello HomeGroup Internet Options Windows Firewall	Access files and printers located on other network con Troublemoot protitiens Diagnose and repair network problems, or get trouble		
corega Open Network and Sharing Ce	nter				
This copy or windows					
🔺 🍡 🗊 🐗 🌗	4:08 AM 8/11/2009				

Network and Sharing Center You can also use the Network and Sharing Center control panel in Windows (Network and Internet) to connect to any available wireless networks.

Figure 7 - 9 Click Taskbar Icon Menu & Network and Sharing Center

- 2. You may need to enter a security key for any access point to which you are trying to connect.
- 3. Click to select a network location (e.g. Home, Work or Public).
- 4. Click "View or change settings in Network and Sharing Center" to access further options for the connection.




Figure 7 - 10 Network Location Set

- 5. Click the taskbar icon and to see any currently connected networks.
- 6. To disconnect from the wireless network you can click the taskbar wireless icon *all*, click the active connection and then click **Disconnect** (button).



沁

Security Enabled Networks

You should try to make sure that any network you are connecting to is a secure network.

Connecting to unsecure networks may allow unauthorized access to your computer, documents, websites and files etc.

Figure 7 - 11 Click Taskbar Icon Menu - Disconnect

Intel® My WiFi Help

R

To get help on Intel® My WiFi configuration and settings, access the Intel® My WiFi Utility from the Start menu (Start > Programs/All Programs > Intel PRO-Set Wireless > Intel My WiFi Technology), or by clicking the notification area icon Click the Help icon Chelp and select a help topic from the Contents menu.

Intel® My WiFi Configuration


Intel® My WiFi Technology uses your WLAN (**for Intel WLAN modules only**) module to allow you to connect up to eight other WiFi enabled devices (e.g. digital cameras, other computers, cell phones, handheld devices etc.) to your computer (similar to Bluetooth), while still connecting to the Internet through your WiFi wire-less connection. Intel® My WiFi Technology offers greater range and speed than other personal area networks, and does not require an access point.

Intel® My WiFi Configuration

You can configure the My WiFi settings as follows.

- Access the Intel® My WiFi Utility from the Start menu (Start > Programs/All Programs > Intel PROSet Wireless > Intel My WiFi Technology), or by doubleclicking the notification area icon .
- 2. Click **Enable** (on the first run of the program there will be no connected devices listed).





- 3. Click Start and click Control Panel.
- 4. Click Network and Sharing Center (Network and Internet).
- 5. Click Change adapter settings.




Figure 7 - 13 Network and Sharing Center 6. Right-click Wireless Network Connection and select Properties.






Figure 7 - 14 **Network Connections**

- 7. Click Sharing (tab) and select "Allow other network users to connect through this computer's Internet connection".
- 8. Select Wireless Network Connection under Home networking connection.
- 9. Click OK.





- Access the Intel® My WiFi Utility from the Start menu (Start > Programs/All Programs > Intel PROSet Wireless > Intel My WiFi Technology), or by doubleclicking the notification area icon .



Figure 7 - 16 Intel® My WiFi Utility - Profiles

Figure 7 - 17 Profiles



R

Profiles that are **preset may not be fully editable**. To edit all the profile settings, click **New** to create a new profile and adjust the settings to your preferences.

Figure 7 - 18 Intel® My WiFi Profile Settings -General 12. Click **Profiles**, click **Intel Wireless PAN** and click **Edit** or **New (Note that all preset settings may not be editable - see sidebar)**.



13. You can change the **Profile Name** and **Network Name** to your personal preferences in **General** (tab).

Profile and Network Names

The **Profile Name** is the name as displayed on your computer in the **Network Connections** control panel (see *Figure 7 - 19 on page 7 - 35*).

The **Network Name (SSID)** is the name the devices see when they try to connect to your computer.

General Security Sharing Advanced	
Profile Name:	
My Profile	
Network Name (SSD):	
My Notebook	
The Profile Name is the name for the Intel® My WiFi computer (Example: Home or Office). The Network 1 device will see when connecting to this network.	

- 14. Click **Security** (tab).
- 15. Change the **Security Type** to **WEP** and the **Encryption Type** to **64bit**.
- 16. Enter a password (8 characters long) in the **Password** box.

Profile Settings	🕜 Help
eneral Security Sharing Advanced	
Security Type: WPA2-PSK	*
Encryption Type: AES-CCMP	-
Password Wireless Security Password (Encryption Key);	
Devices must use the Security Password entered ab My WiFi Access Point.	nove to connect to the Intel®



7

Security

- 17. Click Sharing (tab).
- 18. It is recommended that the **Filter Network Traffic** and **DHCP and DNS Server** are **Disabled**.





Figure 7 - 20 Intel® My WiFi Profile Settings -Sharing

- 19. Click Advanced (tab).
- 20. It is recommended that the **Default Channel** is set to **Channel 1, 6** or **11**.
- 21. Click **OK** to save the settings.





7

- 22. Double-click Wireless Network Connection in Network Connections.
- 23. Click **Details** to display the **Network Connection Details**.




Figure 7 - 22 Wireless Network Connection Details

- 24. Access the Intel® My WiFi Utility from the Start menu (Start > Programs/All Programs > Intel PROSet Wireless > Intel My WiFi Technology), or by clicking the notification area icon .
- 25. To add a new device follow the instructions in the devices' user guide for connecting to a WiFi network.
- 26. Click Add New Device in Intel® My WiFi Utility to confirm the security settings detail.



Figure 7 - 23 Intel® My WiFi Utility (Add New Device)

Intel WLAN & Bluetooth Combo Module High-Speed Data Transfer Configuration


You will need to configure the following settings to enable high-speed wireless data transfer as supported by Intel Wireless LAN & Bluetooth Combo modules (note this information applies to Intel WLAN & Bluetooth Combo modules only).


1. Go the *Windows* control panel and double-click **Device Manager** (in **Hardware** and **Sound** under **Devices and Printers**).



Figure 7 - 24 **Devices and Printers** (Device Manager)

- 2. Click Network adapters to expand the sub-menu.
- 3. Double-click the Intel WiFi Link module.
- 4. Click Advanced (tab).
- 5. Click 802.11n Channel Width for band 2.4 under "Property:".
- 6. Click the pull-down menu under "Value:"
- 7. Click to select Auto.
- 8. Click **OK** and close the control panels.





Windows Mobility Center

The **Windows Mobility Center** control panel provides an easy point of access for information on battery status, power plans used and wireless device status etc.

To access the Windows Mobility Center:

- 1. Click Start, and click Control Panel (or point to Settings and click Control Panel).
- 2. Double-click Windows Mobility Center (Mobile PC).
- 3. Click the button to **Turn wireless off/on**, or click the icon **and** to access the network menu.



Figure 7 - 26 Windows Mobility Center

Fingerprint Reader Module

(Optional)

The **fingerprint reader Protector Suite Software** provides a high level of security for your computer. A further level of security and control is provided in the BIOS (see *"Security Menu" on page 5 - 11*).

The fingerprint reader and Protector Suite Software allow you to:

- Access or Lock your computer
- Protect sensitive files
- Display and file your favorite web pages
- Fill in frequently used dialogs
- Run your favorite applications

If you have included the fingerprint reader in your purchase option you will need to install the driver as per the instructions below.

Make sure you have administrator's rights to your computer, and have a *Windows* password enabled for full security protection.

迩

Password Warning

If you set passwords for any of the security modules, **NEVER** forget your password.

The consequences of this could be serious. If you cannot remember your boot password you must contact your vendor and you may lose all of the information on your hard disk.

Fingerprint Reader Driver Installation

- 1. Insert the *Device Drivers & Utilities* + *User's Manual* disc into the CD/ DVD drive.
- 2. Click **Option Drivers**.
- 3. Click **3.Install FingerPrint Driver > Yes**.
- 4. Click **Next > Next > Next**.
- 5. Click **Finish > Yes** to restart the computer.
- 6. Click the tray icon scan a finger or click **Start > Programs/All Programs > Protector Suite > Control Center and** then begin the enrollment process (see over).

User Enrollment

- Click Start > Programs/All Programs > Protector Suite > Control Center, or double click the notification area icon [2] (click Initialize).
- 2. On the first run of the program you will be asked to click the **Accept** button to accept the license.
- If you have not set a *Windows* password you will be prompted to do so (note: If you have not set a password Protector Suite cannot secure access to your computer).
- 4. Click Submit when you have entered password.
- 5. You will then be prompted to enroll your fingerprints (you can click **Tutorial** to get help with fingerprint enrollment at any time).






Figure 7 - 27 Fingerprint Enrollment



ommended that you enroll more than one finger in case of injury etc.

7

Figure 7 - 28 **Fingerprint Status**

- 6. Click the button above any of the fingers to begin the enrollment process for that finger.
- 7. Swipe the finger until the progress bar reaches **100%** to enroll that finger.
- 8. Repeat the process for all the fingers you wish to enroll (see sidebar), and then click **Save and Continue**.
- 9. Enter a backup password and click Apply.
- 10. Close the fingerprint status window.

Control Center Home Identity Applications	Not set 😑 Change	
Applications		
	Not set	-
ettings jelp		1
Weak 🛥	Strong	1
Apply		
ecommendations: Fingerprint logon	Set 🚺 Change	
Register Automatic backup	Set 🧿 Change	
Number of enrolled fingers:	3 O Change	
Application or driver update	No information 🧿 Change	
With enrolled fingers you can use fingerprint applications:	1	
F1 100 0		
s 👫 👫 🥻		
1 ¹⁰ - 1 ¹² - 1 ¹⁰		

- 11. Right-click the taskbar icon and select Start Control Center (and then swipe a finger) to allow you to Edit Fingerprints, register Applications, edit Settings and access the Help menu etc. You can also run the Control Center etc. from the Protector Suite item in the Programs/All Programs menu
- 12. Click "Help" in Control Center Home to get more information on any topic.
- 13. You can also run the Tutorial, or Product Tour video to get more information.



Figure 7 - 29 Control Center & Biomenu

Modules

- 14. See "Help" on page 7 48 for further details.
- 15. If you swipe your finger over the reader at any time you can access the **Biomenu** to **lock the computer**, **register websites**, access the **Personal Safe**, open the **Control Center** and access the **Help** menu.



For more information on these and other features simply access "**Help**" in the **Fingerprint Control Center** and select the item from the menu on the left.

Fingerprint Control Center Features

Application Launcher

The **Application Launcher** allows you to register applications to be launched when assigned to a particular finger. Simply copy the application icon on to one of the registered fingers and ten click OK to close the application window. Once registered the application will launch when you swipe the appropriate finger across the sensor.

Password Bank

The **Password Bank** stores registrations of user names, passwords and other settings for web sites etc.

Personal Safe

The **Personal Safe** is an encrypted area assigned on your hard drive that allows you to store files and folders to be protected by fingerprint protection.

Bluetooth Module

If your purchase option includes the Combination Wireless LAN & V3.0 Bluetooth module (either Intel® Centrino® Wireless-N 1030, Intel® Centrino Advanced-N 6230 or 3rd Party) then install the driver as instructed.

If your purchase option includes a **standard V2.1 Bluetooth module**, then the operating system's **Bluetooth Devices** control panel is used to configure the Bluetooth settings in *Windows 7*, and therefore does not require a driver.

Ø

Bluetooth Data Transfer

Note that the transfer of data between the computer and a Bluetooth enabled device is supported in one direction only (simultaneous data transfer is not supported). Therefore if you are copying a file from your computer to a Bluetooth enabled device, you will not be able to copy a file from the Bluetooth enabled device to your computer until the file transfer process from the computer has been completed. 泛

Wireless Device Operation Aboard Aircraft

The use of any portable electronic transmission devices aboard aircraft is usually prohibited. Make sure the module(s) are OFF if you are using the computer aboard aircraft.

Use the **Fn + F12** key combination to toggle power to the Bluetooth module, and check the LED indicator to see if the module is powered on or not (see **Table 1** - 3, on page 1 - 11/ Table 1 - 2, on page 1 - 9).

Use the Fn + F12 key combination or **Touch Sensor Instant Key to toggle power to the Bluetooth module**. When the Bluetooth module is powered on the **LED** will be highlighted and the indicator **will briefly be displayed**.

- For **3rd party Bluetooth V2.1** +**EDR modules** see "*Standard Bluetooth Configuration in Windows 7" on page 7 - 60* (no driver is required).
- For **3rd party Bluetooth combo modules** see "3rd Party Bluetooth Combo Driver Installation" on page 7 51 and "3rd Party Bluetooth & WLAN Combo Settings" on page 7 52.
- For Intel Bluetooth combo modules see "Intel Bluetooth Combo Driver Installation" on page 7 - 59 and "Standard Bluetooth Configuration in Windows 7" on page 7 - 60.

3rd Party Bluetooth Combo Driver Installation

Note this driver is required only for the combo Bluetooth and WLAN module only.

- Before installing the driver make sure the Bluetooth module is powered 1. on (use Fn + F12 key combination), then insert the Device Drivers & Utilities + User's Manual disc into the CD/DVD drive. If a Found New Hard*ware* window appears, click **Cancel** in all windows that appear, and then proceed to install the driver as below.
- 2. Click **Option Drivers** (button).
- 3 Click **4.Install Combo BT Driver > Yes**.
- 4. Choose the language you prefer and click **OK**.
- 5. Click Next.
- 6. Click the button to accept the license and click **Next**.
- 7. Click **Next** > (select if you want to create an icon to appear on the desktop) Next > Install.
- 8. Click **Finish**.
- 9. The **My Bluetooth** icon **b** will appear on the desktop and the **Bluetooth** item will be installed in the Programs/All Programs menu.
- 10. See "3rd Party Bluetooth Networking Setup" on page 7 55 for information on Bluetooth networking.

R

High Speed Bluetooth Data Transfer

The Combination Wireless LAN & V3.0 Bluetooth module supports high speed (V3.0) data transfer. However to achieve such transfer speeds. both devices must support high speed data transfer.

(V3.0)

on.

Check your Bluetooth compatible device's documentation to confirm it supports high speed data transfer.

modules are powered




The Bluetooth module's default state will be off after resuming from the **Sleep** power-saving state. Use the key combination (Fn + F12) to power on the Bluetooth module after the computer resumes from Sleep.

> *Figure 7 - 30* My Bluetooth Settings

3rd Party Bluetooth & WLAN Combo Settings


This information applies to the combo Bluetooth and WLAN module only.

- 1. Make sure the Bluetooth module is powered on.
- 2. Double-click the **My Bluetooth** application on the desktop (or access it from the **Programs/All Programs** menu).
- 3. Click My Bluetooth Settings (menu heading).




- 5. Click **OK** to confirm the settings.

2 8	General Settings Setup computer's Bluetooth discovery settings.
Device	Address: 00:1C:7B:0B:8F:1F
The cor	nputer name that other Bluetooth devices will see:
RD1A	1-PC
The dev	vice type that other Bluetooth devices will see:
Laptop	· •
Allow	W Bluetooth devices to find this computer
Sho	w Bluetooth icon in system tray
Noti	fy me about Bluetooth connections
Enal	ble high speed mode support
V Noti	fy me about high speed mode switching



7

- 6. Click File Transfer Settings to Enable sharing of my files with other Bluetooth devices.
- 7. Click **OK** to confirm the settings.







3rd Party Bluetooth Networking Setup

This information applies to the combo Bluetooth and WLAN module only.

- 1. Make sure the Bluetooth module is powered on.
- 2. Double-click the **My Bluetooth** application on the desktop (or access it from the **Programs/All Programs** menu).
- 3. Click My Bluetooth Settings (see Figure 7 30 on page 7 52).





Modules

- 4. Click Network Settings (make sure the Bluetooth module is powered on.
- 5. Click Enable Bluetooth Network and click OK.
- 6. A message will appear in the notification area to confirm that the network driver has been installed.



B

The Bluetooth module's default state will be off after resuming from the **Sleep** power-saving state. Use the key combination (**Fn + F12**) to power on the Bluetooth module after the computer resumes from Sleep.

> Figure 7 - 34 My Bluetooth Devices

3rd Party Bluetooth & WLAN Combo Module Configuration Setup your Bluetooth Device so the Computer Can Find it

- 1. Turn your Bluetooth device (e.g. PDA, mobile phone etc.) on.
- 2. Make the device discoverable (to do this check your device documentation).

To Turn the Bluetooth Module On

1. Press the Fn + F12 key combination to power on the Bluetooth module.

To Add a Bluetooth Device

- 1. Double-click the **My Bluetooth** application on the desktop (or access it from the **Programs/All Programs** menu).
- 2. Double-click the device you want to pair with the computer (if no devices appear press **F5** or click the **Refresh** button to search for devices).



3. You will then be presented with a menu of options to select from.



Figure 7 - 35 Bluetooth Device Options

4. Click the appropriate button to connect to the device.

- 5. You may need to allow the connection from your device, and you will then need to provide a passcode from the device.
- 6. You can then enter the passcode on the computer and click **OK** to establish the connection.





Figure 7 - 36 Bluetooth Pairing Code & Connection Established

Intel Bluetooth Combo Driver Installation

Note this driver is required only for the Intel combo Bluetooth and WLAN module only.

- Before installing the driver make sure the Bluetooth module is powered on (use Fn + F12 key combination), then insert the *Device Drivers & Utilities* + *User's Manual* disc into the CD/DVD drive. If a *Found New Hardware* window appears, click Cancel in all windows that appear, and then proceed to install the driver as below.
- 2. Click **Option Drivers** (button).
- 3. Click **4.Install Combo BT Driver > Yes**.
- 4. Click **Next** > **Next**.
- 5. Click the button to accept the license and click Next.
- 6. Click **Next > Finish**.
- 7. See over for configuration instructions.

Note that, at the time of going to press, **Intel® Centrino® Wireless-N 1030** and **Intel® Centrino Advanced-N 6230** WLAN & Bluetooth V3.0+HS combo modules use the standard Bluetooth configuration in *Windows 7* (see "*Intel Bluetooth Combo Driver Installation*" on page 7 - 59). Do not use the Bluetooth & WLAN Combo settings information outlined from page 7 - 52 to page 7 - 58. See also "*Intel® WLAN & Bluetooth V3.0+HS Combo Modules*" on page 8 - 17.

l

High Speed Bluetooth Data Transfer

The Combination Wireless LAN & V3.0 Bluetooth module supports high speed (V3.0) data transfer. However to achieve such transfer speeds, both devices must support high speed data transfer.

To obtain high speed (V3.0) data transfer make sure that both the WLAN and Bluetooth modules are powered on.

Check your Bluetooth compatible device's documentation to confirm it supports high speed data transfer.

Add a Device

R

Click Start, and click Control Panel and then click Devices and Printers (Hardware and Sound). Click Add a device to search for any available Bluetooth devices.

Bluetooth Module & Resuming From Sleep Mode

The Bluetooth module's default state will be off after resuming from the **Sleep** power-saving state. Use the key combination (**Fn** + **F12**) to power on the Bluetooth module after the computer resumes from Sleep.

Figure 7 - 37 Bluetooth Devices & Click Icon Menu


Standard Bluetooth Configuration in Windows 7

Setup your Bluetooth Device so the Computer Can Find it

- 1. Turn your Bluetooth device (e.g. PDA, mobile phone etc.) on.
- 2. Make the device discoverable (to do this check your device documentation).

To Turn the Bluetooth Module On


- 1. Press the **Fn + F12** key combination to power on the Bluetooth module.
- 2. A Bluetooth icon 📓 will appear in the notification area.
- 3. You can then do any of the following to access the **Bluetooth Devices** control panel.
 - Double-click the notification area icon 🐉 to access the Bluetooth Devices control panel.
- Click/Right-click the notification area icon 月 and choose an option from the menu.



Right-Click Notification Area Icon 😹

To Add a Bluetooth Device

- 1. Access the Bluetooth Devices control panel and click Add a device.
- 2. Double-click the device you want to pair with the computer.







Figure 7 - 38 Add a Device

3. On first connection the computer will provide you with a pairing code to be entered onto the device.

7



- 5. *Windows* will check to see if any drivers are required to complete the pairing.
- 6. Follow any on-screen instructions on the computer if device drivers are required to be installed.

Enter the code into your Bluetooth enabled device and follow any on-screen

7. Click Close.

4.




Figure 7 - 40 Pairing Complete & Bluetooth Device Enabled

7 - 62 Bluetooth Module

To Change Settings for the Bluetooth Device

- 1. Click the notification area icon and select **Show Bluetooth Devices**.
- 2. Right-click on the device you want to change and click **Properties** to:
- Change the name of the device (click Bluetooth, type a new name and click OK).
- Enable/Disable a service (click Services, clear/tick the check box next to the service and click OK).

To Make your Computer Discoverable to Bluetooth Devices

- 1. Click the notification area icon and select **Open Settings**.
- 2. Click **Options**, and make sure that **Allow Bluetooth devices to find this computer** check box (**Discovery**) has a tick inside it.
- 3. Make sure that the *Alert me when a new Bluetooth device wants to connect* check box (**Connections**) has a tick inside it, if you want to be notified when a Bluetooth device wants to connect.

	oth Setting:		
Options	COM Ports	Hardware	
Disc	overy		
1	Allow Blueto	oth devices to find this computer	ł.
4		t your privacy, select this check b a Bluetooth device to find this co	
Con	nections		
3	Allow Blueto	oth devices to connect to this co	mputer
12	Alert me who	en a new Bluetooth device wants	to connect
	ge settings fo	n a Bustooth mabled deuse.	
Chang			estore Defaults
Chang		E	festore nerauits

Bluetooth Help

ß

To get help on Bluetooth configuration and settings, select **Help and Support** from the **Start** menu. Type Bluetooth in the **Search Help** box, and select an item from the returned search results to get more information.

Figure 7 - 41 Bluetooth Settings -Options



Note that **THX TruStudio Pro will be disabled** when you are connecting to an external display through an **HDMI connection**.

THX TruStudio Pro Audio

Install the **THX TruStudio AP** to allow you to configure the audio settings to your requirements for the best performance in games, music and movies. Press the THX TruStudio Pro Touch Sensor Instant Key \checkmark to toggle the **THX TruStudio AP** On/Off.

THX TruStudio AP Installation

- 1. Insert the *Device Drivers & Utilities* + *User's Manual* disc into the CD/ DVD drive.
- 2. Click **Option Drivers** (button).
- 3. Click **5.Install THX TruStudio AP > Yes**.
- 4. Choose the language you prefer and click Next.
- 5. Click **Yes** to accept the license.
- 6. Click Next.
- 7. Click **Full Installation** (button).
- 8. Click **Next > Finish** to restart the computer.

THX TruStudio Pro Activation

On the first run of THX TruStudio Pro you will need to activate the application.

- 1. To activate the application you will need to be connected to the internet.
- 2. Double-click the **THX Activate** icon **the desktop and click the Activate** button.
- 3. The program will connect to the internet to verify the activation key.
- 4. Click Finish to complete the application activation.
- 5. Restart the computer after the process is complete.

THX TruStudio Pro Application

The application can be run from the shortcut in the **Start** menu (**Start > All Programs >Creative > THX TruStudio Pro Settings**).





THX TruStudio Pro Menu

Figure 7 - 42

THX Control Panel

Each control has an On/Off button to allow you to enable/disable the control, and most controls feature a slider to adjust the levels (the subwoofer may be turned on/ off).



- Surround: Provides virtual sound channels to control the level of immersion.
- Crystalizer: Enhances audio to make it sound livelier.
- **Speaker:** Enhances the bass level of the sound system.
- **Smart Volume:** Minimizes sudden volume changes to avoid the need for constant adjustment.
- Dialog Plus: Enhances dialogue levels for movies etc.

Figure 7 - 43 THX TruStudio Pro Controls

THX TruStudio Pro & HDMI

- 1. When you connect an HDMI display to the HDMI-Out port, the THX Tru Studio Pro controls will be disabled.
- 2. A warning box will pop-up and will prompt "Do you want to select another audio device now?".
- 3. Click **No** to continue using the HDMI audio output from your external display (do not attempt to select another audio device when connected to the external HDMI display).

HX TruStudio Pro Settings		
The current selected audio device is disa application, or has unplugged jack conr audio device now?		
	<u>Y</u> es	No

Figure 7 - 44 THX TruStudio Pro HDMI Display Warning

Chapter 8: Troubleshooting

Overview

Should you have any problems with your computer, before consulting your service representative, you may want to try to solve the problem yourself. This chapter lists some common problems and their possible solutions. This can't anticipate every problem, but you should check here before you panic. If you don't find the answer in these pages, make sure you have followed the instructions carefully and observed the safety precautions in the preface. If all else fails, talk to your service representative. You should also make a record of what happened and what remedies you tried.

Of course, if something goes wrong, it will happen at the most inconvenient time possible, so you should preview this section just in case. If, after you've tried everything, and the system still won't cooperate, try turning it off for a few minutes and then rebooting. You will lose any unsaved data, but it may start working again. Then call your service representative.

Basic Hints and Tips

Many of the following may seem obvious but they are often the solution to a problem when your computer appears not to be working.

- **Power** Is the computer actually plugged into a working electrical outlet? If plugged into a **power strip**, make sure it is actually working. Check the **LED Power Indicators** (see "*LED Indicators*" on page 1 7) to see the computer's power status.
- Connections Check all the cables to make sure that there are no loose connections anywhere.
- Power Savings Make sure that the system is not in Hibernate or Sleep mode by pressing the keys configured in your Power Options (see "Configuring the Power Buttons" on page 3 8), the Fn + F4 key combination, or power button to wake-up the system.
- **Brightness** Check the brightness of the screen by pressing the **Fn** + **F8** and **F9** keys to adjust the brightness (see *Table 1 3, on page 1 11*).
 - Display Choice Press Fn + F7 to make sure the system is not set to "external only" display.
 - Boot Drive Make sure there are no optical media and/or USB storage devices in any connected drive when you start up your machine (this is a common cause of the message "Invalid system disk Replace the disk, and then press any key" / "Remove disks or other media. Press any key to restart").

Backup and General Maintenance

- Always **backup** your important data, and keep copies of your OS and programs safe, but close to hand. Don't forget to note the **serial numbers** if you are storing them out of their original cases, e.g. in a CD wallet.
- Run **maintenance programs** on your hard disk and OS as often as you can. You may schedule these programs to run at times when you are not using your computer. You can use those that are provided free with your OS, or buy the more powerful dedicated programs to do so.
- Write down your passwords and keep them safe (away from your computer). This is especially important if you choose to use a **Boot** password for the SCU (see *"Security Menu" on page 5 11*).
- Keep copies of vital **settings files** such as network, dialup settings, mail settings etc. (even if just brief notes).



The CPU is not a user serviceable part. Opening this compartment, or accessing the CPU in any way, may violate your warranty.

Viruses

- Install an **Anti-Virus** program and keep the **definitions file** (the file which tells your program which viruses to look for) up to date. New computer viruses are discovered daily, and some of them may seriously harm your computer and cause you to lose data. **Anti-Virus** programs are commercially available and the **defini-tions file updates** are usually downloadable directly from the internet.
- Be careful when opening e-mail from sources you don't know. **Viruses** are often triggered from within **e-mail attachments** so take care when opening any attached file. You can configure most **Anti-Virus** programs to check all **e-mail attachments**. **Note**: You should also beware of files from people you know as the virus may have infected an **address book** and been automatically forwarded without the person's knowledge.
- Keep a "Bootable CD-ROM/DVD-ROM/USB storage device" (this CD/DVD/USB device provides basic information which allows you to startup your computer) handy. You may refer to your OS's documentation for instructions on how to make one, and many Anti-Virus programs will also provide such a disk (or at least instructions on how to make one).

Upgrading and Adding New Hardware/Software

- Do not be tempted to make changes to your **Windows Registry** unless you are very sure of what you are doing, otherwise you will risk severely damaging your system.
- Don't open your computer or undertake any repair or upgrade work if you are not comfortable with what you are doing.
- Read the **documentation**. We can assume, since you are reading this that you are looking at the computer's manual, but what about any new peripheral devices you have just purchased? Many problems are caused by the installation of new hardware and/or software. Always refer to the documentation of any new hardware and/or software, and pay particular attention to files entitled "**READ ME**" or "**READ ME FIRST**".
- When installing a new device always make sure the device is powered on, and in many cases you will need to restart the computer. Always check that all the cables are correctly connected.
- Make sure you have installed the **drivers** for any new hardware you have installed (latest **driver files** are usually available to download from vendor's websites).
- Thoroughly check any **recent changes** you made to your system as these changes may affect one or more system components, or software programs. If possible, go back and undo the change you just made and see if the problem still occurs.

• Don't over complicate things. The less you have to deal with then the easier the source of the problem may be found; **Example** - if your computer has many devices plugged into its ports, and a number of programs running, then it will be difficult to determine the cause of a problem. Try disconnecting all of the devices and restarting the computer with all the peripheral devices unplugged. A process of elimination (adding and removing devices and restarting where necessary) will often find the source of a problem, although this may be time consuming.

Problems & Possible Solutions

Problem	Possible Cause - Solution
You turned the power on but it doesn't work.	<i>Battery missing / incorrectly installed.</i> Check the battery bay, make sure the battery is present and seated properly (the design of the battery only allows it to go in one way). Make sure there's nothing interfering with the battery contacts.
The Battery LED power indicator (, is blinking orange.	Low Battery. Plug in the AC power source. If the computer doesn't start up immediately, turn it off then on again.
You are losing battery power too quickly.	 The system is using too much power. If your OS has a Power Options scheme (see "Power Plans" on page 3 - 4) check its settings. You may also be using an ExpressCard device/USB device/external device that is drawing a lot of power. You are attempting to run an SLI configuration on battery power. Due to the high power and system demands created by enabling SLI Configuration, you should not enable SLI configuration if your computer is powered by battery only.
Actual battery operating time is shorter than expected.	The battery has not been fully discharged before being recharged. Make sure the battery is fully discharged and recharge it completely before reusing (see "Battery Information" on page 3 - 10). Check the settings of any active power plan (see "Power Plans" on page 3 - 4). A peripheral device/USB device is consuming a lot of power. Turn off/remove the unused device to save power.

Problem	Possible Cause - Solution
The computer feels too hot.	Make sure the computer is properly ventilated and the vents/fan intakes are not blocked. If this doesn't cool it down, put the system into Hibernate mode or turn it off for an hour. Make sure the computer isn't sitting on a thermal surface (see <i>"Overheating" on page 1 - 16</i>). Make sure you're using the correct adapter.
	Make sure that your notebook is completely powered off before putting it into a travel bag (or any such container). Putting a notebook which is powered on in a travel bag may cause the vents/fan intakes to be blocked.
Nothing appears on screen.	The system is in a power saving mode. Toggle the Fn + F4 (see "Configuring the Power Buttons" on page 3 - 8).
	<i>The screen controls need to be adjusted.</i> Toggle the screen control Fn + F8/F9 key combinations. If you're connected to an external monitor, make sure it's plugged in and turned on. You should also check the monitor's own brightness and contrast controls.
	The computer is set for a different display. Toggle the screen display key Fn + F7 combination. If an external monitor is connected, turn it on.
	The screen saver is activated. Press any key or touch the TouchPad.
No image appears on the external monitor I have plugged in and powered on.	You haven't installed the video driver and configured it appropriately from the Control Panel . See "NVIDIA Video Driver Controls" on page B - 1 for instructions on installing and configuring the video driver.

Problem	Possible Cause - Solution
You forget the boot password.	If you forget the password, you may have to discharge the battery of the CMOS. Contact your service representative for help.
	Password Warning
	password, NEVER forget your password. The consequences of this could be serious. If you cannot word you must contact your vendor and you may lose all of the information on your hard disk.
The sound cannot be heard or the volume is very low.	The volume might be set too low. Check the volume control in the Volume Control Panel in the Windows taskbar, use the key combination Fn + F5 and F6 or move your finger slowly along the volume control slider to adjust the system volume (see "Audio Features" on page 2 - 9/"Touch Sensor Instant Keys" on page 1 - 9) to adjust.
The CD/DVD cannot be read.	The compact disc is dirty. Clean it with a cleaner kit.
The Optical Disk Drive tray will not open when there is a disc in the tray.	The disc is not correctly placed in the tray. Gently try to remove the disc using the eject hole (see "Loading Discs" on page 2 - 3).
The DVD regional codes can no longer be changed.	The code has been changed the maximum 5 times. See "DVD Regional Codes" on page 2 - 5.

Problem	Possible Cause - Solution
The TouchPad doesn't work.	The Touchpad has been disabled. Press the Touchpad toggle (Fn + F1) key combination (make sure you have installed the Touchpad driver.
I am sliding my finger up and down on the right side of the TouchPad to scroll a Window and the TouchPad does not respond.	There are different TouchPad versions available on this computer, and this version requires tapping/holding to scroll. Either tap repeatedly, or hold the finger down, at the top or bottom right of the touchpad (depending on the scrolling direction required) to scroll the window.
The system freezes or the screen goes dark.	The system's power saving features have timed-out. Use the AC/DC adapter, press a key on the keyboard, or press the sleep (Fn + F4) key combination, or press the power button if no LEDs are lit.
The system never goes into a power saving mode .	Power Options features are not enabled. Go to the Windows Power Options menu and enable the features you prefer (see <i>"Power-Saving States" on page 3 - 6</i>). Make sure you have enabled Hibernate mode from the control panel.
The Wireless LAN/ Bluetooth/PC Camera modules cannot be detected.	The modules are off. Check the appropriate Touch Sensor indicator to see if the modules are on or off (see "Touch Sensor Instant Keys" on page 1 - 9). If the LED indicator is not illuminated, then press the appropriate touch sensor instant key/function key combination in order to enable the modules.
The Wireless LAN/ Bluetooth/PC Camera modules cannot be configured.	The driver(s) for the module(s) have not been installed. Make sure you have installed the driver for the appropriate module (see the instructions in Chapter 7 " Modules " for the appropriate module).

Problem	Possible Cause - Solution
When a DVD is played in Windows Media Player/ Media Center, the audio track in other languages (commentaries etc.) is not clear if connected to the S/PDIF-Out Jack.	This is an issue with Windows Media Player/Media Center and audio output through the S/PDIF- Out Jack. We recommend that you use the Power DVD application to play DVDs.
Nothing appears on the screen when the PC Camera software is run.	You have selected an external display as the default display device. The PC Camera application software needs to be run while the default notebook LCD is the selected display device. After a camera picture is obtained on the default notebook LCD, you may then use the Fn + F7 to toggle through the display modes (give the screen time to refresh). If you have selected an external display as your display device do not run the PC Camera software application until you have switched back to the notebook LCD.
A file cannot be copied to/from a connected Bluetooth device.	The transfer of data between the computer and a Bluetooth enabled device is supported in one direction only (simultaneous data transfer is not supported) . If you are copying a file from your computer to a Bluetooth enabled device, you will not be able to copy a file from the Bluetooth enabled device to your computer until the file transfer process from the computer has been completed
The Bluetooth module is off after resuming from Sleep.	The Bluetooth module's default state will be off after resuming from the Sleep power-saving state. Use the key combination $(Fn + F12)$ to power on the Bluetooth module after the computer resumes from Sleep.

Problem	Possible Cause - Solution
No sound can be heard through an HDMI connected display device.	You have not configured the HDMI audio output. See "HDMI Audio Configuration" on page B - 18.
You have a RAID	You may need to recover the RAID volumes.
enabled and the system will not boot to <i>Windows</i> .	 As the computer starts up press Ctrl + i to enter RAID configuration menu If the RAID volume's Physical disks are marked in red, then press 4.Recovery Volume Options. If you cannot access 4.Recovery Volume Options (i.e. it is grayed out) then press 5.Acceleration Options. Press Enter and return to the main menu, then press 4.Recovery Volume Options. Follow the on screen instructions to recover the Physical disks. If only one of the physical disks now appears green, then press 6.Exit to save the changes and exit and boot to Windows. When Windows is loaded run the Intel® Matrix Storage Console from the Intel® Matrix Storage Manager in the Programs/All Programs menu. Click View > Advanced Mode. Right-click on the RAID volume and select either Verify Volume Data or Verify and Repair Volume Data. The verification or verification and repair process will run and display progress. A dialog box will display the final status of the verification or verification and repair status.

Problem	Possible Cause - Solution
The computer is off (or in Sleep Mode) but powered by the AC/DC adapter plugged in to a working outlet, or by battery with a capacity above 20%. I have plugged a device into the powered USB port in order to charge it, but the device is not charging.	The port is not powered on. Toggle power to the port using the Fn + power button combination. This function may not work with certain external USB compliant devices (check your device's doc- umentation). If this is the case, power the computer on and connect the external USB device in order to charge it.

Bluetooth Connection Problems

If you are experiencing problems connecting to some Bluetooth devices (in particular certain mobile phones and headsets) it maybe necessary to download and install the **Windows Mobile Device Center** software (for *Windows Vista* and *Windows 7*). Go to the Microsoft website and search for the **Microsoft Windows Device Center Driver for** *Windows Vista* (64-bit or 32-bit) and Windows 7 (64-bit or 32-bit), and then download the driver.

- 1. Install the *Microsoft Windows Device Center Driver* as appropriate for your operating system.
- 2. *Windows Vista* will automatically configure the driver for you, however *Windows* 7 requires further configuration.
- 3. Make sure the Bluetooth device is powered on.
- 4. Go the *Windows 7* control panel and double-click **Device Manager** (Hardware and Sound > Devices and **Printers**).
- 5. Bluetooth Peripheral Device(s) will be listed under Other Devices (note this will only be listed if you have connected, or tried to connect to, a Bluetooth device previously).





- 6. Right-click **Bluetooth Peripheral Device** and click on **Update Driver Software**.
- 7. Click Browse my computer for driver software.
- 8. Click Let Me pick from a list of device drivers on my computer.

😡 🚊 Update Driver Software - Bluetooth Peripheral Drivice	🙄 Updete Driver Software - Bluetooth Peripheral Device
How do you want to search for driver software? Search automatically for updated driver software Windows will search your computer and the Internet for the Litter driver software	Browse for driver software on your computer Search for driver software in this location:
for you device, unless you've disabled this feature in your device installation settings.	Jockude subfielders Let not provide a subfield drive software compatible with the device, and all driver, This lat will show installed drive subhave compatible with the device, and all driver,
Cancel	Not Cencel

Figure 8 - 2 - Browse my computer.../Let me pick from...

9. Select Bluetooth Radios from the list.



Troubleshooting

- 10. A list of drivers will appear with **Manufacturer** on one side and **Model** in the other.
- 11. Choose Microsoft Corporation (make sure you choose the full name Microsoft Corporation and do not choose Microsoft - Note that you must have installed the Microsoft Windows Device Center Driver for **Microsoft Corporation** to appear in the list).
- 12. Select Windows Mobile-based device support from the Model list.




Figure 8 - 4 - Select Device Driver

13. Click **Next > Yes** and the driver will install.

Make sure you select

14. Click **Close** to complete the installation.

8 - 16 Bluetooth Connection Problems

- 15. The **Device Manager** should now display the **Windows Mobile-based device support** under **Bluetooth Radios**.
- 16. You will need to repeat the process for any other Bluetooth Peripheral Devices listed under Other Devices.




Figure 8 - 5 - Device Manager - Bluetooth Radio

Troubleshooting

Intel® Centrino Advanced WLAN & Bluetooth V3.0+HS Combo Modules

Note that, at the time of going to press, **Intel® Centrino® Advanced-N 6230 or Intel® Wireless-N 1030** WLAN & Bluetooth V3.0+HS combo modules use the standard Bluetooth configuration in *Windows 7* (see *"Standard Bluetooth Configuration in Windows 7" on page 7 - 38*). **Do not use** the Bluetooth & WLAN Combo settings information outlined from page 7 - *30* to page 7 - *36*.

Driver Release Update

Note also that, at the time of going to press, this module does not support high speed Bluetooth (V3.0) data transfer. **Intel** have scheduled a driver release to allow this module to support high speed data transfer, so please check with Intel or your service center for details.

Installing Windows 7 (pre Service Pack 1) for RAID Systems with Advanced Format Disks

The following information is only applicable under the following conditions:

- You are configuring your SATA hard disks in a **RAID**.
- You are using **Advanced Format hard disks** that have a **4KB physical sector size**.
- You are using a *Windows* 7 version that **DOES NOT include Service Pack 1** on the DVD disc.

Windows 7 versions **pre Service Pack 1** (i.e. those that do not include the installation of Service Pack 1 from the actual DVD disc) require a driver to support Advanced Format hard disks with a 4KB physical sector size when used in a RAID.

This driver is included on the *Device Drivers & Utilities* + *User's Manual disc* but you will need to go to an operable computer and copy the driver to a USB Flash drive, external USB hard disk or external floppy disk drive and floppy diskette, as it is required as part of the *Windows 7* system installation process.

- 1. Go to the operable computer and insert a USB Flash drive, external USB hard disk or external USB floppy disk drive and floppy diskette.
- 2. Insert the Device Drivers & Utilities + User's Manual disc into the CD/DVD drive of the operable computer.
- Copy the f6flpy-x** folder from the location below (D: denotes your DVD drive) on the *Device Drivers & Utilities + User's Manual* disc to the USB Flash drive, external USB hard disk or floppy diskette.
- For Windows 7 32bit = D:\Option\06RAID\f6flpy-x86
- For Windows 7 64bit = D:\Option\06RAID\f6flpy-x64

Troubleshooting

- Press a key at system startup to begin installing *Windows* from your *Microsoft Windows* 7 disc (make sure the DVD device is set at the top of the **Boot Sequence** in the BIOS - see "Boot Sequence (Boot Menu)" on page 5 - 14).
- 5. Click Install Now.
- 6. Make sure your USB Flash drive, external USB hard disk or external USB floppy disk drive and floppy diskette is attached to one of the USB ports on the computer.
- 7. Click "I accept the license terms" tickbox and click Next.
- 8. Click Custom (advanced).
- 9. Click to select Load Driver when the "Where do you want to install Windows?" screen appears.
- Click Browse and browse to the location you copied the files to on your USB Flash drive, external USB hard disk or external USB floppy disk drive and floppy diskette (X: denotes your USB Flash drive, external USB hard disk or external USB floppy disk drive):
- Windows 7 32bit X:\f6flpy-x86\iaStor.inf
- Windows 7 64bit X:\f6flpy-x64\iaStor.inf
- 11. Click **Next** (or format the drive to your preferences).
- 12. Follow the on-screen instructions to install the *Windows* **7** operating system.
- Install the Windows drivers from the Device Drivers & Utilities + User's Manual disc as per Table 4 1, on page 4 3 (make sure you install the Intel Rapid Storage Technology driver see "IRST Driver Installation" on page 7 8).

Appendix A: Interface (Ports & Jacks) Overview

The following chapter will give a quick description of the ports & jacks which allow your computer to communicate with external devices, connect to the internet etc.

Ports and Jacks

ltem	Description	
Card Reader	The card reader allows you to use the following digital storage cards:	
	MMC (MultiMedia Card)RS MMC (requires PC adapter)SD (Secure Digital)Mini SD (requires PC adapter)MS (Memory Stick)MS Duo (requires PC adapter)MS (Memory Stick Pro)Source PC adapter)	
DC-In Jack	Plug the supplied AC/DC adapter into this jack to power your computer.	
DVI-Out Port	The DVI-Out (Digital Visual Interface) Port is a video connector interface. This allows you to connect an external monitor, TV or Flat Panel Display etc. as a display device (see <i>"Configuring an External Display (NVIDIA)" on page B - 7</i>) by means of a DVI cable. If you are using an older type of monitor you will need to use a converter to convert the signal from DVI to VGA.	
e-SATA/USB Port e-SATA / •←	This is a combined e-SATA (external Serial Advanced Technology Attachment)/ USB 2.0 compatible port.	
	Plug external Serial ATA hard drives into this e-SATA (external Serial Advanced Technology Attachment) port. See "USB 2.0/1.1 Ports*" on page A - 5 for USB port information.	

Interface (Ports & Jacks)

Item	Description
HDMI-Out Port HDMI	The HDMI-Out (High-Definition Multimedia Interface) port is an audio/video connector interface for transmitting uncompressed digital streams. This allows you to connect an external monitor, TV or Flat Panel Display etc. as a display device (see <i>"Configuring an External Display (NVIDIA)" on page B - 7</i>) by means of a HDMI cable. Note that HDMI carries both audio and video signals (see <i>"HDMI Audio Configuration" on page B - 18</i>).
Headphone-Out Jack	Headphones or speakers may be connected through this jack. Note : Set your system's volume to a reduced level before connecting to this jack.
Line-In Jack	The Line-In jack allows you to play audio sources through the computer's speakers. Note that audio input through Line-in will default to the mute setting. To set up your audio sources to play through the Line-in jack go to the Sound represented the control panel and make sure the Mute box is not ticked.
Microphone-In Jack	Plug an external microphone in to this jack to record on your computer.

Interface (Ports & Jacks)

ltem	Description
Mini-IEEE 1394 Port	This allows high-speed connection to various peripheral devices, e.g. external disk drives and digital cameras (see note below).
1394	IEEE 1394 The Mini-IEEE 1394 ports only support SELF POWERED IEEE 1394 devices.
RJ-45 LAN Jack	This port supports LAN (Network) functions. Note: Broadband (e.g. ADSL) modems usually connect to the LAN port.
S/PDIF-Out Jack	This S/PDIF (Sony/Philips Digital Interface Format) Out Port allows you to connect your DVD- capable PC to a Dolby AC-3 compatible receiver for "5.1" or 'dts' surround sound.
Security Lock Slot	To prevent possible theft, a Kensington-type lock can be attached to this slot. Locks can be purchased at any computer store.

Interface (Ports & Jacks)

ltem	Description
USB 2.0/1.1 Ports*	These USB (Universal Serial Bus) 2.0 compatible ports (USB 2.0 is fully USB 1.1 compliant) are for low-speed peripherals such as keyboards, mice or scanners, and for high-speed peripherals such as external HDDs, digital video cameras or high-speed scanners etc. Devices can be plugged into the computer, and unplugged from the computer, without the need to turn the system off (if the power rating of your USB device is 500mA or above, make sure you use the power supply which comes with the device).
3.0	This model has two USB 3.0 ports on the left side of the computer which are denoted by their blue color. USB 3.0 will transfer data much faster than USB 2.0, and is backwards-compatible with USB 2.0. The USB 3.0 port requires a driver installation (see <i>"USB 3.0" on page 4 - 7</i>).
	*Note: The powered USB 2.0 port (see <i>"Left View" on page 1 - 14</i>) may be toggled on /off by means of the Fn + Power Button key combination. When the powered USB port is on it will supply power when the system is off but still powered by the AC/DC adapter plugged into a working outlet, or powered by the battery with a capacity level above 20% (this may not work with certain devices - see page 8 - 13).

Appendix B: NVIDIA Video Driver Controls

The basic settings for configuring the LCD are outlined in "Video Features" on page 1 - 18.

NVIDIA Video Driver Installation

Make sure you install the drivers in the order indicated in *Table 4 - 1, on page 4 - 3*.

- 1. Insert the *Device Drivers & Utilities + User's Manual* disc and click *Install Drivers* (button).
- 2. Click 2.Install nVIDIA VGA Driver > Yes.
- 3. Click **AGREE AND CONTINUE** (button) to accept the terms of the license agreement.
- 4. Click Next.
- 5. Click the **RESTART NOW** button to restart the computer.

After Video (VGA) driver has been installed, and the system restarted, the OS will automatically run the "Winsat.exe" to rate the performance. Allow time for this process to finish and do not restart during this process (if you have restarted the system see *"Windows Update" on page 4 - 9*).

Video Card Options


Note that card types, specifications and drivers are subject to continual updates and changes. Check with your service center for the latest details on video cards supported (see "Video Adapter Options" on page C - 2, or contact your service center for details).



NVIDIA Control Panel


More advanced video configuration options are provided in the **NVIDIA Control Panel** tab.

- 1. Click Start, and click Control Panel (or point to Settings and click Control Panel).
- 2. Double-click **NVIDIA Control Panel** (click "**Classic View**" from the left of the menu if you are in **Control Panel Home**).



B - 2 NVIDIA Control Panel

The **NVIDIA Control Panel** provides additional video configuration controls and tools which allow quick access to features such as display configuration, 3D Settings and Help menus etc.




Navigating the Control Panel

ß

Navigate through the control panels in much the same way as you would a web page. Click on the sub-heading tasks in the left menu (and on the highlighted links) for information. Use the buttons on the top left to go back, forward etc.

> Figure B - 2 NVIDIA Control Panels

The **Help** menus provide index and search features, and direct links to the NVIDIA website etc.





Display Devices

Note that you can use a DVI cable connected to the DVI-Out port, or an HDMI (High-Definition Multimedia Interface) cable connected to the HDMI-Out port to connect an external display (if you are using an older type of monitor you can use a converter to convert the signal from DVI to VGA). See your display device manual to see which formats are supported.

- 1. The built-in LCD.
- 2. An external display connected to the DVI-Out Port.
- 3. An external display/TV (if the TV supports an HDMI connection) connected to the HDMI-Out Port.

Display Devices

ß

Besides the built-in LCD, you can also use an external monitor/flat panel display as your display device. The display options are:

- The built-in LCD.
- An external display connected to the DVI-Out port.
- An external display connected to the HDMI-Out port.

Note that HDMI supports video and audio signals.

Note that **THX TruStudio Pro will be disabled** when you are connecting to an external display through an **HDMI connection**.

DO NOT use the **Fn + F7** key combination to toggle through display options when SLI is enabled.I



SLI Configuration & Multiple Displays

Note that if SLI configuration is enabled only a **Single** display may be used as the display device.

DO NOT use the **Fn** + **F7** key combination to toggle through display options when SLI is enabled. SLI supports only a **Single** display, and attempting to configure dual displays may cause an error. Use the NVID-IA control panel to select the display to be used.

Display Modes

Single Display Mode

Only one of your displays is used.

Duplicate Displays

Duplicate simply shows an exact copy of the Primary display desktop on the other display(s). This mode will drive multiple displays with the same content.

Extend Desktop

Extend Desktop treats both connected displays as separate devices, and they act as a virtual desktop resulting in a large workspace. When enabled, you can drag any icons or windows across to the other display desktop. It is therefore possible to have one program visible in one of the displays, and a different program visible in the other display.

Display Not Shown

If the attached display

does not appear in the "1.Select the displays

you want to use." win-

dow, click "My Display

is not shown " and

then click the appropri-

ate button to force de-

tection of the missing

Figure B - 4

Set Up Multiple


Displays

display.

Configuring an External Display (NVIDIA)

You can use the NVIDIA control panel to configure any attached displays.

- 1. Attach your external display to the DVI-Out Port or HDMI-Out port, and turn it on.
- 2. Go to NVIDIA Control Panel (see page B 2).
- 3. Double-click **Display** (if the sub-menus are not visible), and then click **Set up multiple displays**.
- 4. Any attached display will appear under "1.Select the displays you want to use."




- 5. Click the tickbox alongside any display you wish to use.
- 6. Click **Apply > Yes** to save any changes made (the **Apply** button will appear in the bottom right of the control panel when changes have been made).



Β

Duplicating the Displays

- 1. Attach your external display to the DVI-Out Port or HDMI-Out port, and turn it on.
- 2. Go to NVIDIA Control Panel (see page B 2).
- 3. Double-click **Display** (if the sub-menus are not visible), and then click **Set up multiple displays**.
- 4. Any attached display will appear under "1.Select the displays you want to use."
- 5. Click the tickbox alongside any display you wish to use.
- 6. Right-click one of the display icons and click "**Duplicate displays...**" (select which is to be the primary display) to duplicate the desktop on both displays.




- 7. Click Apply > Yes to save any changes.
- B 8 Configuring an External Display (NVIDIA)

Figure B - 5 Duplicate Displays

Extending the Display

- 1. Attach your external display to the DVI-Out Port or HDMI-Out port, and turn it on.
- 2. Go to NVIDIA Control Panel (see page B 2).
- 3. Double-click **Display** (if the sub-menus are not visible), and then click **Set up multiple displays**.
- 4. Click to select a primary display under "1.Select the displays you want to use."
- 5. Right-click one of the display icons and click "**Extend desktop on this display....**" to extend the desktop across both displays.



Changing the Primary Display on Extended Displays

R


If you want to switch the primary display if the displays are extended then right-click the secondary display icon. Select "Make this the Windows main display". Click Apply > Yes to save the change (see over).

Figure B - 6 Extend the Display

6. Click **Apply > Yes** to save any changes.

Changing the Primary Display on Extended Displays

- 1. If you want to switch the primary display if the displays are extended then rightclick the **secondary** display icon.
- 2. Select Make this the Windows main display.
- 3. Click **Apply > Yes** to save the change.



and select Make this the Windows main display.

B - 10 Configuring an External Display (NVIDIA)


Figure B - 7 Switch Primary Display

Attaching Other Displays (Win 7)

Configuring an External Display in Windows 7

- 1. Attach your external display to the DVI-Out Port or HDMI-Out port, and turn it on.
- 2. Go to the Screen resolution control panel.
- 3. Click the **Detect** button.
- 4. The computer will then detect any attached displays.

Change the appeara	ince of your display	
		Detegt
Display: 1 2. M	Iultiple Monitors 👻	
Resolution: 1680	× 1050 🔻	
Orientation: Lands	cape 👻	
Multiple displays: Dupli	cate these displays 🔹	
This is currently your main	ı display.	Advanced settings
Connect to a projector (or	press the 👪 key and tap P)	
Make text and other items What display settings show		



(Win 7)

Β

🦷 « All Control Panel Items 🕨 Display 🕨 Screen Resolution	👻 🍫 Search Control Panel
Change the appearance of your display	
	Detect [dentify]
Digplay: 1 2. Multiple Monitors Resolution: 1680 × 1050	
Orientation:	
Multiple displays Duplicate these displays Duplicate these displays This is currently you Extend these displays Show desktop only on 1	Advanced settings
Connect to a project Show desktop only on 2 tap of Make text and other news larger or smaller	
What display settings should I choose?	

5. You can configure the displays from the **Multiple Displays** menu.

- Duplicate these displays Shows an exact copy of the main display desktop on the other display(s)
- Extend these displays Treats both connected displays as separate devices
- Show desktop only on 1/2 Only one of your displays is used.

Figure B - 9 Screen Resolution Multiple Display Options (Win 7)

Using the Windows Logo Key 🝙 + P Key Combination to Switch Displays

You can also use the $\mathbf{a} + \mathbf{P}$ key combination to quickly change display configuration and modes (this is particularly useful when attaching a projector) in *Windows* 7.

- 1. Attach your external display to the external monitor port and turn it on.
- 2. Press the $\mathbf{x} + \mathbf{P}$ key combination.
- 3. An on-screen menu will pop up.
- 4. Use the cursor keys (or $\mathbf{r} + \mathbf{P}$) to select the appropriate configuration from the menu, and press Enter to confirm the selection.



Figure B - 10 + P Display Configuration Selection (Win 7)

NVIDIA Video Driver Controls

Video Card Options

ß


Note that card types, specifications and drivers are subject to continual updates and changes. Check with your service center for the latest details on video cards supported. Note that not all video card options for this computer model series support SLI configura-(see "Video tion Adapter Options" on page D - 2, or contact vour service center for details).

> *Figure B - 11* Set SLI Configuration

SLI Multi GPU Configuration

This computer features an **NVIDIA Scalable Link Interface (SLI)** that improves graphic quality and performance by combining **dual** NVIDIA GPUs (two video cards are required) in a single system. To enable/disable SLI Configuration:

- 1. Go to NVIDIA Control Panel (see page *B* 2).
- Click "+" next to 3D Settings if its sub-items are not shown and then click Set SLI and PhysX configuration.



- 3. Click "Maximize 3D Performance" under "SLI configuration:".
- 4. Click to select "PhysX settings; Auto-select (recommended) is the default setting.
- 5. Click Apply and Restart Now to restart the computer (see over).
- **B** 14 SLI Multi GPU Configuration

SLI Multi GPU Configuration & Battery Power

Note that due to the high power and system demands created by enabling SLI Configuration, **you should not enable SLI configuration if your computer is powered by battery only**. If you attempt to run an SLI configuration when the computer is powered by the battery only, then system problems may occur.

- If the computer is currently powered by battery only **do not enable SLI config-uration**.
- If you have currently enabled SLI configuration, and the computer is powered by the AC/DC adapter, **do not switch to battery power only** (or go to the NVIDIA Control Panel and disable SLI configuration before switching to battery power only).

众

SLI Configuration & Multiple Displays


Note that if SLI configuration is enabled only a **Single** display may be used as the display device.

DO NOT use the **Fn** + **F7** key combination to toggle through display options when SLI is enabled. SLI supports only a **Single** display, and attempting to configure dual displays may cause an error. Use the NVID-IA control panel to select the display to be used.

Manage 3D Settings

You can configure the 3D **global settings** (to be applied to all application programs) or make specific adjustments for installed **program settings**.

- 1. Go to NVIDIA Control Panel (see page B 2).
- 2. Click Manage 3D Settings and select either Global Settings or Program Settings.
- 3. Click the **Setting** menu items to select any global options required, or **select a program to customize** from the drop-down menu (click **Add** to add any program that does not appear in the menu).
- 4. Click **Apply** to save the settings.







Adjust Video Settings

You can adjust video color and image settings from the Video sub-menus.

- 1. Go to NVIDIA Control Panel (see page B 2).
- 2. Click "+" next to Video if its sub-items are not shown and then click either Adjust video color settings or Adjust video image settings.
- 3. Make any adjustments required for any display and click **Apply** to save the settings.







HDMI Audio Configuration

As HDMI (High-Definition Multimedia Interface) carries both **audio** and video signals you can configure the audio output from the **NVIDIA control panel** and **Sound** control panel. The settings will depend upon the external HDMI display you have connected to.

When you connect a display to the HDMI-Out Port then the **Set up digital audio** item will appear under **Display**. Click *"Change Windows Sound Settings"* (button) to access the **Sound** control panel.







Audio Setup for HDMI


In some cases it will be necessary to go to the Sound control panel and manually configure the HDMI audio output.

- 1. Click Start, and click Control Panel (or point to Settings and click Control Panel).
- 2. Click Sound 💿 (Hardware and Sound).
- 3. Click Playback (tab)
- 4. The playback device will be selected.
- 5. You may need to select the audio device and click Set Default (button).
- 6. Double-click the device to access the control panel tabs.





- 7. Adjust the HDMI settings from the control panel tabs.
- 8. Click **OK** to close the **Sound** of control panel.



The following audio formats are currently supported: Nax Number of Channels: 2 HDCP: Supported Bit Depths: 3upported Bit Depths: 44.0 Sample Rates: 44.1 bit: 40.0 ktc Encoded Formats: No compressed formats found. OK Cancel ASUS V/C266H-1 Properties: General Supported Formats Levels Enhancements Adva Default Format Safett the sample rate and bit depth to be used when	ASUS VK2	66H-1	
HDCP: Supported Bit Depth:: 16 bit Sample Rates: 44.1 6% Encoded Formats: No compressed formals found. OK: Cancel ASUS VK200H-1 Properties. General: Supported Formats Service the sample rate and bit depth to be used when Service the sample rate and bit depth to be used when	The following audio form	mats are currently support	e di:
Bit Depths: 36 bit 24-bit Sample Rates: 441 641 Ensoded Formats: No compressed formats found. CK Cancel ASUS VK260H-1 Properties: General Formats Levels Enhancements Adva Default Formats Levels Enhancements Adva	Max Number of Channel	s: 2	
24-bit Sample Rates: 441 Mit 450 Mit; 450 Mit; Encoded Formats: No compressed formats found. CK: Cancel ASUS VK266H-1 Properties: General Supported Formats [Levels Enhancements Adva Default Format Cells in Formats	HDCP:	Supported	
Sample Rates: 441 14t1 460 14t2 Encoded Formats: No compressed formats found. OK Cancel ASUS VK266H-1 Properties: General Supported Formats Levels Enhancements Adva Default Format Select the sample rate and bit depth to be used when	Bit Depths:		
I A Liste 40.0 kH; Encoded Formats: No compressed formats found. OK Cancel ASUS VK266H-1 Properties. Serieral Supported Formats Levels, Enhancements Adva Dorbuth Format Select the sample rate and bit depth to be used when	Sample Rates:		
48.0 kHz Encoded Formats: No compressed formats found. OK Cancel ASUS VK/260H-1 Properties: General Supported Formats Levels Enhancements Adva Orfault Format			
Ne compressed formats found. OK Cancel ASUS VK/260H-1 Properties. General Supported Formats Levels Enhancements Adva Orfault Format Select the sample rate and bit depth to be used when	48.0 kHz		
No compressed formats found. OK Cancel ASUS V/C266H-1 Properties. General Supported Formats Levels Enhancements Adva Default Format Select the sample rate and bit depth to be used when	Encoded Formats		
OK Cancel ASUS V/266H-1 Properties: Seneral Supported Tomats Levels Enhancements Adva Default Format Select the sample rate and bit depth to be used when		found.	
	General Supported Formats Default Format	s Levels Enhancements	
misnarcu node.	in shared mode.	and bit depth to be used	ATTET FUTUR
16 bit, 48000 Hz (DVD Quality)	16 bit, 48000 Hz (DVD	Quality)	Iest
16 bit, 44100 Hz (CD Quality)	16 hit, 44100 Hz (CD Q	uality	
E 2 and 44100 Hr (Studio Quality) E 2 and 44100 Hr (Studio Quality) 24 and 44100 Hr (Studio Quality) Z4 and 48000 Hz (Studio Quality) Z4 allow applications to take exclusive control of this e If allow applications to take exclusive control of this e If allow applications to take exclusive control of this e	E 24 bit, 44100 Hz (Studio	o Quality)	this device

Figure B - 16 HDMI Device Properties

HDMI Notes

- Connect a device with HDMI support to the HDMI-Out port **BEFORE** attempting to play audio/video sources through the device.
- Under certain conditions, if the HDMI cable is disconnected, the default audio playback device will not revert to speakers until the computer is restarted (if you do not wish to restart the computer then go to the **Sound** control panel and select **Speakers** as the default audio playback device).

HDMI Video Configuration

- 1. Connect an HDMI cable from the HDMI-Out port to your external display.
- Configure your external display as per the instructions in "Configuring an External Display (NVIDIA)" on page B - 7.
- 3. Set up your external display (TV or LCD) for HDMI input (see your display device manual).
- 4. You can now play video/audio sources through your external display.

THX TruStudio Pro & HDMI

- 1. When you connect an HDMI display to the HDMI-Out port, the THX TruStudio Pro controls will be disabled.
- 2. A warning box will pop-up and will prompt "Do you want to select another audio device now?".
- 3. Click **No** to continue using the HDMI audio output from your external display (do not attempt to select another audio device when connected to the external HDMI display).


Ø

Other Applications

If you are using a third party application to play DVDs etc. you will need to consult the application's documentation to see the appropriate audio configuration (the application must support digital to analog translation).

HDCP Status

If your external display is HDCP (High Bandwith Digital Content protection) compatible then the NVIDIA control panel will display the HDCP system status.





Appendix C: Specifications

Latest Specification Information

B

The specifications listed in this Appendix are correct at the time of going to press. Certain items (particularly processor types/ speeds and CD/DVD device types) may be changed, updated or delayed due to the manufacturer's release schedule. Check with your service center for details.

Specifications

Processor	Core Logic	Video Adapter Options
Note all processor packages are rPGA988B	Intel® HM67 Chipset Display	nVIDIA® GeForce GTX 560M PCIe Video Card 1.5GB GDDR5 Video RAM On Board
Intel® Core i7-2920XM (2.5GHz) - Extreme Quad-Core Mobile Processor 8M L3 Cache, 32nm (32 Nanometer), DDR3-1600MHz, TDP 55W	18.4" (46.74cm) FHD (1920 * 1080) 16:9 TFT LCD (Embedded Light Sensor Controls Panel Automatically)	Supports Microsoft DirectX® 11.0 Supports HDCP Supports DVI Dual Link Supports HDMI 1.4a NVIDIA PhysX™
Intel® Core i7-2820QM (2.3GHz) Quad-Core Mobile Processor 8M L3 Cache, 32nm (32 Nanometer),	Dual Channel DDRIII (DDR3) *Three 204 Pin SO-DIMM Sockets	GeForce CUDA™ Technology Supports nVIDIA® SLI Technology
DDR3-1600MHz, TDP 45W	Supporting DDRIII (DDR3) 1333/1600**	BIOS
Intel® Core i7-2720QM (2.2GHz) Quad-Core Mobile Processor 6M L3 Cache, 32nm (32 Nanometer),	MHz Memory Modules *Memory Expandable up to 12GB Compatible with 2GB or 4GB Modules **Note: 1600 MHz Memory Modules are	One 32Mb SPI Flash ROM AMI BIOS
DDR3-1600MHz, TDP 45W		**Note: 1600 MHz Memory Modules are Storage
Intel® Core i7-2630QM (2.0GHz) Quad-Core Mobile Processor 6M L3 Cache, 32nm (32 Nanometer), DDR3-1600MHz, TDP 45W	only supported by Quad-Core CPUs to a maximum of two SO-DIMMs.	Up to three (Factory Option) Changeable 2.5" 9.5 mm (h) SATA (Serial) Hard Disk Drives supporting RAID level 0/1/5 <i>Note 1st & 2nd HDDs are in SATA III</i> <i>interface</i>

One 12.7 mm Super Multi/Blu-Ray Combo/Blu-Ray Writer SATA Optical Device Drive (Factory Option)

Specifications

Audio	Card Reader	Interface
High Definition Audio	Embedded Multi-In-1 Card Reader	Four USB 2.0 Ports
S/PDIF Digital Output	- MMC / RSMMC	(Note: One USB2.0 port on the left side
Built-In Microphone	- SD / Mini SD / SDHC / SDXC	can supply power when the system is off
5.1 Channel Speakers (with Sub woofer)	- MS / MS Pro / MS Duo	but still powered by the AC/DC adapter
THX Surround Sound	Note: Some of these cards require PC	plugged into a working outlet, or powered by the battery with a capacity level above
7.1CH Audio output supported by	adapters that are usually supplied with	20% - see "USB 3.0 Ports & Powered
headphone, microphone, S/PDIF & Line- In Jack	the cards.	USB 2.0 Port" on page 1 - 14)
III Jack		Two USB 3.0 Ports
Keyboard & Pointing Device	Slots	One eSATA Port (SATA Interface, USB
Full Size Winkey Isolated Keyboard with	One ExpressCard™/34/54 Slot	2.0 Combo)
Numeric Keypad		One Mini-IEEE1394a Port
Tamono Roypad	One Mini Card Slot for WLAN or WLAN &	One DVI-Out Port
Built-In TouchPad (with Multi Gesture	Bluetooth Combo Half Mini-Card Module	One HDMI-Out (High-Definition
Functionality)	with PCIe & USB Interface	Multimedia Interface) Port (with HDCP Support)
Eight Touch Sensor Instant Keys (Light		One Headphone/Speaker-Out Jack
Sensor Control, CCD, Bluetooth, WLAN,		One Microphone-In Jack
Internet, Silent Mode, Sound Effect,		One S/PDIF Out Jack
Mute)		One Line-In Jack
Eight Gaming Keys G1 ~ G8		One RJ-45 LAN Jack
W/A/S/D Game Key Marking		One DC-In Jack

Specifications

Communication	Security	Environmental Spec
Built-In 10/100/100 Base-TX Ethernet LAN Intel® Centrino® Ultimate-N 6300 3*3 (802.11 a/g/n) Half Mini-Card PCIe WLAN Module (Factory Option)	Security (Kensington® Type) Lock Slot BIOS Password Fingerprint Reader Module (Factory Option)	Temperature Operating: 5°C - 35°C Non-Operating: -20°C - 60°C Relative Humidity
Intel® Centrino® Advanced-N 6230 2*2 (802.11 a/g/n) Half Mini-Card PCIe WLAN +	Operating System Windows® 7 with Service Pack 1	Operating: 20% - 80% Non-Operating: 10% - 90% Physical Dimensions & Weight
Bluetooth V3.0+HS Combo Module (Facto- ry Option)	Power Management	439mm (w) * 299mm (d) * 44mm - 65mm (h)
Intel® Centrino® Wireless-N 1030 1*2 (802.11 b/g/n) Half Mini-Card PCIe WLAN +	Supports Wake on LAN Supports Wake on USB	5.6kg with Battery and ODD
Bluetooth V3.0+HS Combo Module (Facto- ry Option)	Power	
Bluetooth 2.1 + EDR (Enhanced Data Rate) Module (Factory Option)	Full Range AC/DC Adapter – AC in 100 - 240V, 50 - 60Hz DC Output 19V, 11.57A (220 Watts)	
Combo WLAN (802.11b/g/n) and Bluetooth v3.0 Half Mini-Card Module (Factory Option)	Removable 8 Cell Smart Lithium-Ion 89.21WH Battery Pack	
2.0M Pixel PC Video Camera Module		